

# LW 8441A

4U rack mount LCD workstation  
7" LCD W/touch screen  
3 x hot-swappable SATA HD tray



## » Features

- » 4U rackmount compact design, only 20.6" depth
- » 7" 800x480 LCD panel W/touch screen
- » 3 x hot-swappable SATA HD tray
- » Intel socket-775 Core 2 Duo / Dual core ATX system
- » on-board video/Audio/LAN
- » built-in 84-key keyboard drawer with 2-button track-ball
- » 300W PS/2 ATX power supply

## » Specifications

### Material:

Heavy Duty Cold Rolled Electroplated Steel  
EIA RS-310C 19" Rackmount Standard

### LCD Panel W/touch screen:

Size: 7"  
Resolution: 640x480  
Front 5 button monitor control and rear VGA input  
Resistive-type touch screen with USB connector

### Standard ATX mother board:

Processor:  
Intel Socket-775 Core 2 Duo processor, 667/1066/1333FSB  
Memory: 4 x DDR2 memory socket (up to 8GB)  
On board Intel Graphic  
On board Ethernet LAN / Audio  
Integrated one IDE / 6 SATA port  
4 x USB ports  
1 x parallel port  
2 x PS/2 ports mouse/keyboard

### Devices:

3 open hot-swappable SATA tray  
1 x 5.25" open drive bay

### Expansion slot:

7 x open expansion slots  
1xPCI-E(x16), 3xPCI-E(x1), 3xPCI

### Front panel controls:

Power on/off switch  
System reset button  
2 x USB ports  
2 x LED indicator for power/HD-activity

### Keyboard and track ball:

84 key Keyboard that slides from the bottom of the chassis  
(rear PS/2 type connector)  
2-buttons trackball (rear PS/2 connector)

### Cooling fan:

Front chassis:  
2 x 92mm (51CFM each)

### Rear chassis:

Optional for 2 x 60mm (23.5CFM)

### Power supply:

300W PS/2 ATX power supply  
Optional for 400W/500W power supply

### Cable:

1 x 6' cable for VGA connector

### Color:

Black

### Operation Temperature:

0°C to 50°C

### Weight:

50 lb

### Dimension:

19"(W) x 20.6"(D) x 7"(H)

## » Ordering Guide

### LW 8441A:

4U rack mount LCD workstation comes with 7" 800x480 LCD panel with touch screen, Intel socket-775 Core 2 Duo processor system.

## » Options

**ACNODES**

14628 Central Blvd, Chino, CA  
91710  
tel: 909.597.7588, fax: 909.597.1939

© Copyright 2011 Acnodes, Inc.  
All rights reserved. Product description and product specifications are subject to change without notice. For latest product information, please visit Acnodes' web site at [www.acnodes.com](http://www.acnodes.com).