

MKP-804

8-port Matrix IP KVM Switch 4 User Consoles (1-local/1-remote/2-IP) 1U Rack Mountable



» Specifications

Material:

Metal Housing

KVM Ports Layout:

8 x proprietary DB-15 combo free KVM connector
1 x local console ports (2 x USB and 1 x DB15 VGA port)
2 x remote console port
2 x proprietary cascade ports (1 IN & 1 OUT)
1 x external power input jack

KVM Cables:

8 x 6' proprietary 4-in-1 KVM cables (PS/2 or USB combo free)
Optional for 10, and 15 feet

Local Access:

1 x DB-15 VGA port (resolution up to 1600 x 1200)
2 x USB ports for Keyboard & Mouse

Remote Access:

2 x receiver

IP Console:

2 x IP Access
1 x RJ45 Ethernet
1 x DB-9 serial
1 x USB Port

IP Security:

SSL v3, RSA, AES, CSR, http & https internet access.
1 x active user (15-user login)

Receiver Includes:

1 x RJ-45 port up to 300 meters (1000 feet) Cat6 / Cat5 cable
1 x DB-15 KVM port with 1 x 6' KVM cable for remote computer
1 x DB-15 VGA port for monitor
2 x USB ports for keyboard & mouse
1 x external power input jack

Expansion Options:

Optional 3' Proprietary Cascade Cable

» Features

- » Compact, 1U 8-port matrix IP KVM switch
- » Secure IP remote user access
- » 4 user consoles (1 x local, 1 x remote Cat6 with receiver, 2 x IP access)
- » 16 x proprietary DB-15 combo free KVM connector
- » Combo free KVM port, support PS/2 or USB input devices
- » 8 x 6' proprietary 4-in-1 KVM cables (PS/2 or USB combo free)
- » Optional 3' Proprietary Cascade Cable

Compatibility:

Mix PCs, SUNs, MACs, IBMs, HPs, DELLs server Windows Vista / 2003 / XP / 2000, Linux, Netware, Unix

Power Adapter:

External 100~240VAC, 50/60Hz 0.5A 12VDC output power adapter
Optional for 12/24/48VDC power input

Dimensions:

448mm x 180mm x 44 mm
17.6" x 7.1" x 1.73"

Net Weight/Gross Weight:

9lbs /15lbs

Color:

Black

Temperature:

Operating 0°C to 60°C
Storage -5°C to 60°C

Relative Humidity:

90% non-condensing

Shock:

50G peak acceleration (11 ms, half-sine wave)

Vibration:

58~100Hz / 0.98G (11 ms/ cycle)

Regulatory approval :

FCC, CE

» Ordering Guide

MKP-804:

1U Rack mountable with 8-port Matrix IP KVM Switch, 8 x proprietary DB-15 combo free KVM connectors, and 4 User Consoles (1 x local console, 2 x remote console, and 2 x IP console)

ACNODES

14628 Central Blvd,
Chino, CA 91710
tel: 909.597.7588, fax: 909.597.1939

© Copyright 2011 Acnodes, Inc.
All rights reserved. Product description and product specifications are subject to change without notice. For latest product information, please visit Acnodes' web site at www.acnodes.com.