

PC 5152

15" touch panel PC
Core 2 Duo all-in-one system
1 x PCI-32 expansion slot



» Features

- » 15" 1024x768 LCD panel
- » Resistive type touch screen, RS-232 type
- » NEMA4/IP 65 front beige color aluminum bezel
- » Core 2 Duo/ Dual core 667/800/1066 PC system
- » On-board Video/Dual Gigabit LAN/HD Audio
- » Built-in HD/CD-ROM
- » Wall or panel mount ready
- » One PCI-32 expansion slot

» Specifications

Front panel:

Material Aluminum Front Panel with Steel Chassis
Front Panel NEMA 4 or IP65-rated
White Pantone 413C Color

LCD Panel:

Size: 15" TFT Sunlight Readable
Resolution: 1280 x 768
Luminance: 350 cd/m2
Contrast ratio: 700:1
Viewing Angle(H-V): 145°/125°
Colors: 65G (36 bits)
LCD Panel MTBF: 50,000 hrs

Touch Screen:

5-wire type resistive-type touch screen
3 gram activation pressure
Light transmission 75% typical
Chemical / Solvent/ Abrasion resistant
RS-232 interface

All-in-one System:

CPU: Core 2 Duo, Dual core 533/800/1066MHz FSB
Chipset: Intel 945G + ICH7, AMI BIOS
2 x DDR2 memory socket, 4GB memory (max)
1 x Compact Flash Type 2 socket
1 x 2.5" internal SATA HD drive with anti-shock
1 x slim-type Optical drive, (CD-ROM/DVD RW)
2 x broadcom bcm5787M Gigabit LAN with ASF2.0 remote control
1 x HD Audio Realtek ALC883

Expansion Slot:

1 x PCI-32 half-size expansion slot
1 x PCI-e mini card

System Fan:

2 x 40mm ball bearing cooling fan

Mounting:

Panel/wall mount ready, Optional for rack mount (19" rack cabinet)

I/O Ports:

4 x RS-232 ports, 1 x RS-232/422/485 port
1x parallel port
2 x PS/2 Ports (Keyboard & mouse)
1 x D-sub 15-pin VGA ports
4 x USB ports
2 x RJ45 GbE ports
1 x MIC, 1 x Line-in, 1 x speaker port
1 x Compact Flash slot

Power Supply:

180W ATX power 90~240VAC, 50/60Hz auto switch power supply
Output (max): 3.3V@ 16.8A, 5V@12A, 12V@10A, -12V@0.8A

Weights:

30 lbs

Dimension:

452mm (W) x 356mm (H) x 110mm (D)

Environmental:

Operating/Storage temperature:
0°C to 50°C / -20°C to 60°C
Operating Humidity:
5% to 95%, @ 60°C non-condensing
Vibration:
5 - 17Hz, 0.1" peak-to-peak displacement
17-640Hz, 1.5G acceleration peak-to-peak
Shock: 10G acceleration peak-to-peak (11ms)

Safety:

CE/FCC

» Ordering Guide

PC 5152:

15" touch panel PC, Dual Core 1.8GHz, 1GB memory, 80GB HD, on-board Dual Gigabit LAN/HD audio/Video

» Options

ACNODES

14628 Central Blvd, Chino,
CA 91710
tel: 909.597.7588, fax: 909.597.1939

© Copyright 2011 Acnodes, Inc.
All rights reserved. Product description and product specifications are subject to change without notice. For latest product information, please visit Acnodes' web site at www.acnodes.com.