

RM-9190

19" 1280x1024 LCD screen
Support Sun native resolution
9U rackmount LCD monitor



» Features

- » 9U rackmount monitor panel
- » Bright 1280 x 1024 Active Matrix LCD display
- » Support Sun native resolution
- » Front OSD function for LCD display
- » Panel protected by tempered glass
- » Optional touchscreen function
- » Optional DVI interface

» Specifications

Material:

Heavy-duty steel

LCD Panel:

Size: 19"

Max. Resolution: 1280x1024

Support Sun native resolution (1152x900)

Brightness (cd/m²): White 250 cd/m²

Contrast Ratio: 500:1

Pixel Pitch: 0.098mm x 0.294mm

Response time: Tr=2ms, Tf=10ms

Viewing Angle: 140°(L/R),140°(U/D)

Colors: 16.2M colors

Back Light: Four Lamps

On Screen Control:

Auto-Adjustment for
contrast, balance, H-position,
V-position, phase, brightness

Video Sync:

45~80KHz

Video input port:

D-sub 15-pin VGA port, optional for DVI-D

Front Panel Controls:

Power on/off switch
OSD(on screen display)

Touch Screen(Optional):

5 wires resistive type USB interface or
RS-232 port interface

Screen protection:

LCD panel protected by tempered glass

System Cables:

1 x VGA cable, 1 x DVI cable (opt)

Power source:

100 ~ 240VAC input

Power Consumption:

21.05W

Color:

Black

Environmental:

Temperature:

Operate 0°~ 50°C / 32°~ 122°F

Storage-20°~ 60°C / -4°~ 140°F

Humidity: 10% ~ 90% RH

Gross Weight:

18.2kg / 40.1lb

Dimension:

19"(W) x 15.7"(H) x 2.5"(D)

482.6 x 398.6 x 64mm

Safety:

CE/FCC, UL/CUL certificated

» Ordering Guide

RM 9190:

9U 19" 1280 x 1024 rack mount LCD monitor, Black color
Optional for touch screen and video input

ACNODES

14628 Central Blvd, Chino,
CA 91710
tel: 909.597.7588, fax: 909.597.1939

© Copyright 2011 Acnodes, Inc.
All rights reserved. Product description and product specifications
are subject to change without notice. For latest product information,
please visit Acnodes' web site at www.acnodes.com.