

# RMC 8417A

4U rackmount computer  
Front access I/O  
Front access 7 x expansion slots



## » Features

---

- » 4U rackmount computer, 17.6" depth
- » Intel Socket-775 standard ATX system
- » Front I/O layout
- » Front accessible 7 open expansion slots
- » On board Video, LAN & Audio
- » 1 x 3.5" & slim-type optical device open drive bay
- » 300W ATX PS/2 power supply

## » Specifications

---

### Construction:

Heavy-duty steel cold-rolled steel

### Standard ATX mother board:

#### Processor:

Intel Socket-775 Core 2 Duo processor, 667/1066/1333FSB

Memory: 4 x DDR2 memory socket (up to 8GB)

On board Intel Graphic

On board Ethernet LAN / Audio

Integrated one IDE / 6 SATA port

4 x USB ports

1 x parallel port

2 x PS/2 ports mouse/keyboard

Front I/O layout

### Devices:

1 x 3.5" open HD/FDD drive bay

1 x slim-type optical drive open drive bay

### Expansion slot:

7 x open expansion slots

1xPCI-E(x16), 3xPCI-E(x1), 3xPCI

### Front Panel Controls:

Power on/off switch

System reset button

2 x USB ports

2 x LED indicator for power/HD-activity

### Cooling Fan:

2 x 92mm (51CFM each) cooling fan

Optional for additional 2 x 60mm (23.5CFM each)

### Power supply:

300W 110/220VAC PS/2 type Industrial level Auto-switching power supply

Optional for 400W power supply

### Color:

Black

### Operation Temperature:

0°C (32°F)~ 50°C (122°F)

### Humidity:

5%~95% non-condensing

### Gross Weight:

40lb

### Dimension:

19"(W) x 17.6"(D) x 7.0"(H)

## » Options

---

SL20: 20" slide rail

PS400: 400W ATX power supply

## » Ordering Guide

---

RMC 8417A:

4U ATX rack mount system with Intel Core 2 Duo processor, front I/O layout and front accessible 7 x expansion slots.

**ACNODES**

14628 Central Blvd, Chino, CA  
91710  
tel: 909.597.7588, fax: 909.597.1939

© Copyright 2011 Acnodes, Inc.  
All rights reserved. Product description and product specifications are subject to change without notice. For latest product information, please visit Acnodes' web site at [www.acnodes.com](http://www.acnodes.com).