

RPWQ 1190

**19" 144x900 Wide screen LCD
Support Quad display
1U rack mount monitor drawer**



» Specifications

Material:

Heavy-duty steel, 1U rack mount monitor drawer LCD panel:
Size: 19". wide screen
Resolution: 1440 x 900
Brightness (cd/m²): 300nit
Contrast Ratio: 1000:1
Response Time: 1.3 ms)
Display area:408 x 255, Viewing Angle: 160°x160°
Display color: 16.7M (dithering)
LCD Panel MTBF (hrs): 50,000

LCD resolution mode:

720 x 400 (70Hz), 640 x 480 (60/70/72/75Hz)
800 x 600 (60/70/72/75Hz), 1024 x 768 (60/70/75Hz),
1152 x 864 (60/70/75Hz), 1280 x 720 (60/75Hz), 1280 x
1024 (60/75Hz), 1440 x 990 (60Hz)

Video input single:

VGA single input: Analog RGB 0.7 Vp-p
Sync: Separate H/V, Composite, SOG

Plug & Play:

EDID 1.3

LCD OSD control:

Auto-Adjustment, contrast, brightness clock, phase, H-
position, V-position
Misc: information, OSD timer, color, language, reset

Quad display:

Image system: PAL/NTSC
Resolution: 1024x525 (NTSC)/1024x625 (PAL)
Refresh rate: 60Hz (NTSC)/50Hz (PAL)
Colors: 16.7M
Video input:
Camera: 1.0Vpp, 75 Ohm x 4, VCR: 1.0Vpp, 75Ohm x 1
Video output:
Live monitor: 1.0Vpp, 75 Ohm x 4, Loop: 1.0Vpp, 75Ohm x
4, VCR: 1.0Vpp, 75Ohm x 1
Support: Auto gain control/Time/Date/On screen display
Camera title: 8 character title
Display format: 2 x zoom on playback, Quad, Full, Sequence
Dwell time: 0 to 99 sec adjustable
Build in buzzer and key-lock

ACNODES

14628 Central Blvd, Chino, CA
91710
tel: 909.597.7588, fax: 909.597.1939

» Features

- » 1U rack mount monitor drawer, 25.6" depth
- » 19" 1440 x 900 LCD monitor
- » Support Quad display (NTSC/PAL)
- » Membrane buttons for Quad & OSD function
- » 4 x BNC video IN & OUT channel
- » 1 x RS-232 remote port
- » 110/220VAC power supply

Front panel control:

Membrane buttons for Quad-mode OSD & LCD OSD setup

Connectors:

1 x D-Sub 15-pin VGA, 1 x BNC, 1 x AV video in
4 x BNC video-input , 4 x BNC video-out
1 x BNC VCR-in, 1 x BNC VCR-out,
1 x D-sub 15pin alarm I/O
1 x D-sub 9pin RS-232 remote port

Power supply adapter:

Auto-switching 12V 48W 100~240VAC 50/60Hz power supply

Mounting type:

1U height, pull-out slide rail monitor drawer for 19" rack
cabinet, 2 x thumb screw lock for security

Environmental:

Temperature: Operation: 0 to 50°C, Storage: -5 to 60°C
Relative humidity: 5~90%, non-condensing
Shock: 10G acceleration (11ms duration)
Vibration: 5~500Hz 1G RMS random vibration

Color:

Black

Gross weight:

30lb

Dimension (W x H x D):

19" x 1.73" x 25.6"

Certification:

FCC-A, CE

» Options

» Ordering Guide

RPWQ 1190: 1U 19" 1440x900 rack mount LCD monitor
drawer

© Copyright 2011 Acnodes, Inc.
All rights reserved. Product description and product specifications
are subject to change without notice. For latest product information,
please visit Acnodes' web site at www.acnodes.com.