

# RM 6200

## 20.1" 1600 x 1200 TFT LCD 8U rackmount LCD monitor



### » Features

---

- » 8U compact design, only 3.52" depth
- » 20.1" 1600 x 1200 LCD monitor
- » OSD (On Screen Display) function
- » Tempered glass add for LCD monitor protection
- » Remote 110/220VAC power adapter

### » Specifications

---

**Material:**

Heavy-duty steel

**LCD Panel:**

Size: 20"

Resolution: 1600 x 1200

Brightness (cd/m<sup>2</sup>): 250nit

Contrast Ratio: 700:1

Pixel Pitch: 0.255mm x 0.255mm

Response Time: 25msec

Active Area: 408.0 (H) x 306.0 (V)

Scan Frequencies:

Horizontal 31.47KHz to 68KHz

Vertical 80Hz to 68 Hz

Colors: 16.7M colors

Power Consumption: 45W (type)

**On Screen Control:**

Auto-Adjustment for  
contrast,  
balance

H-position

V-position

phase

brightness

**Front Panel Control:**

Power on/off switch

OSD (on screen control)

**LCD Protection:**

Tempered glass in front of the LCD panel

**Connectors:**

1 x D-Sub 15 pin (female)

1 x DVI (Digital Video Input)

**Power supply:**

Industrial level Auto-switching power supply for  
85V~264V AC input

**Color:**

Black

**Operation Temperature:**

0 to 55 degree C (32 to 131 degree F)

**Weight:**

45lb

**Dimension:**

19"(W) x 3.52"(D) x 14"(H)

### » Options

---

**CB-15:** 15 feet VGA cable

**CB-25:** 25 feet VGA cable

### » Ordering Guide

---

**RM 6200:**

20.1" 1600 x 1200 8U rackmount monitor

**ACNODES**

14628 Central Blvd, Chino,  
CA 91710  
tel: 909.597.7588, fax: 909.597.1939

© Copyright 2011 Acnodes, Inc.  
All rights reserved. Product description and product specifications  
are subject to change without notice. For latest product information,  
please visit Acnodes' web site at [www.acnodes.com](http://www.acnodes.com).