

2U rack mount system Front I/O layout 3 x full size PCI / PCIe slots



» Features

- » 2U rackmount system, 17" depth
- » Core i3 / i5 / i7, Core 2 Duo processor
- » Front accessible I/O layout
- » front accessible PCI / PCIe full-size expansion slots
- » On board Audio/Video/LAN
- » 300W PS/2 ATX power supply

» Specifications

Construction:

Heavy-duty cold-rolled steel.
Inside: zinc-plated with bright chromate,
Outside: texture-coated

ATX M/B:

Dual Core or Core 2 Duo processor, LGA-775
Chipset: Q963
Memory: DDR2 memory, 1GB (up to 8GB)
Core i3 / i5 / i7 processor, LGA-1155
Memory: DDR3 memory, 1GB (up to 8GB)
On-board 10/100/1000BT LAN,
On-board video
On-board Audio
SATA connector
USB 2.0 ports
PS/2 ports

Devices:

1 x slim-type 24X CD-ROM
Optional for DVD/DVD RW
2 x 3.5" hidden drive bay (for 3.5" Hard Drive)

Front expansion slot:

3 x PCI expansion slots
1 x PCI-32 / 1xPCIex1 / 1xPCIex16 (opt) expansion slots
1 x PCI-32 / 2xPCI-ex1 (opt) expansion slots
1 x PCI-ex16 / 2xPCI-ex1 (opt) expansion slots

Front Panel Connector:

2 x USB ports
1 x VGA port, 1 x Audio Line in/out, Mice
1 x RJ-45, 10/100BT LAN port
2 x PS/2 port

Front Panel Controls:

Power on/off switch
System reset button

Cooling Fan:

Front: 2 x 40mm ball-bearing fans
Back: 1 x 80mm all-bearing fan

Power supply:

PS/2 type 300W 110/220VAC power supply

Slide rail (optional):

20" slide rail

Color:

Black

Operation Temperature:

0°C (32°F)~40°C (104°F)

Humidity:

5%~95% non-condensing

Gross Weight:

40lb

Dimension:

19"(W) x 17"(D) x 3.5"(H)

» Options

PS-400: 400W ATX power supply

PS-500: 500W ATX power supply

SL20: 20" slide rail

» Ordering Guide

RMC 7217A:

2U rackmount computer with front I/O, 3 PCI / PCIe full-size expansion slots.