

# APA9150

15 inch 1024 x 768 resistive touchscreen monitor with VGA + DVI + HDMI + DP video input, IP66 rated flat front bezel, and an aluminum die-casting enclosure.

- ▶ Aluminum die-casting chassis
- ▶ Features flat front bezel with IP66 design
- ▶ 15 inch 1024 x 768 Resistive type touch screen monitor
- ▶ 2.15" short depth metal rugged construction
- ▶ Option for Projected Capacitive type touch screen
- ▶ VGA, DVI, HDMI, and DP video input
- ▶ Panel mount or VESA (100mm) mount ready
- ▶ 9 to 36V DC power input w/ external AC power adapter



## Description

Industrial monitor with a 15 inch 1024 x 768 Resistive type touch screen display, VGA + DVI + HDMI + DP video input, aluminum die-casting enclosure, IP66 rated flat front bezel, and panel or VESA (100mm) mount. Option for Projected Capacitive type touch screen and 1000-nits high brightness.

## Technical Specifications

SPECIFICATION	VALUE
<b>Material</b>	Solid aluminum die-casting chassis IP66 compliant flat front panel
<b>LCD Panel</b>	Size: 15 inch Max Resolution: 1024 x 768 Brightness (cd/m <sup>2</sup> ): 300, option for 1000-nit Contrast Ratio (typ) : 2000:1 Viewing Angle (H/V): 176° x 176° Colors: 16.2M MTBF (hrs): 70,000
<b>Video input</b>	1 x VGA 1 x DP 1 x DVI-D (share with HDMI) 1 x HDMI (share with DVI-D)
<b>Touch screen</b>	Resistive type touch screen monitor with USB port (std) Option for Projected Capacitive type touch screen monitor with USB port

*Specifications subject to change without notice.*

<b>Rear panel control</b>	Power on/off switch OSD membrane switch
<b>Mounting Type</b>	Panel mount or VESA (100mm) mount
<b>Connectors</b>	1 x VGA port 1 x DP port 1 x DVI-D port (share with HDMI) 1 x HDMI port (share with DVI-D) 1 x USB Type B for touchscreen 1 x 3-pin terminal block DC power input 1 x 2W speaker (option)
<b>Power supply</b>	Power Input: 9~36V DC power input with external AC power adapter Power Consumption: Max. 9W
<b>Weight</b>	9.48 lb / 4.3 kg
<b>Dimension</b>	16.14"(W) x 12.2"(H) x 2.15"(D)
<b>Environmental</b>	Operating Temperature: 0°C to 50°C Storage Temperature: -30°C to 70°C Relative Humidity: 10~90% @ 40°C, non-condensing Option for -20°C to 60°C wide operating temperature (for standard brightness)
<b>Certification</b>	CE/FCC, Class A

## Available Configurations

### Touch Screen

- 15-inch resistive-type touch screen RS-232 / USB port
- 15-inch Project capacitive-type touch screen USB port

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588  
[www.acnodes.com](http://www.acnodes.com)