

APA9215

21.5" 1920 x 1080 FHD resistive type touchscreen monitor with VGA + DVI + HDMI + DP video input, IP66 rated flat front bezel, and 9 to 36V DC power input.

- ▶ Aluminum die-casting chassis
- ▶ Features flat front bezel with IP66 design
- ▶ 21.5 inch 1920 x 1080 FHD Resistive type touch screen monitor
- ▶ 2.55" short depth metal rugged construction
- ▶ Option for Projected Capacitive type touch screen
- ▶ VGA, DVI, HDMI, and DP video input
- ▶ Panel mount or VESA (100mm) mount ready
- ▶ 9 to 36V DC power input w/ external AC power adapter



Description

Industrial monitor with a 21.5 inch 1920 x 1080 Full HD resistive type touch screen display, VGA + DVI + HDMI + DP video input, and panel or VESA (100mm) mounting holes. The monitor features an aluminum die-casting chassis and IP66 rated waterproof flat front bezel. Option for Projected Capacitive type touch screen and 1000-nits high brightness.

Technical Specifications

SPECIFICATION	VALUE
Material	Solid aluminum die-casting chassis IP66 compliant flat front panel
LCD Panel	Size: 21.5 inch Max Resolution: 1920 x 1080 Brightness (cd/m ²): 250, option for 1000-nit Contrast Ratio (typ) : 3000:1 Viewing Angle (H/V): 178° x 178° Colors: 16.7M MTBF (hrs): 30,000
Video input	1 x VGA 1 x DP 1 x DVI-D (share with HDMI) 1 x HDMI (share with DVI-D)
Touch screen	Resistive type touch screen monitor with USB port (std)

Specifications subject to change without notice.

	Option for Projected Capacitive type touch screen monitor with USB port
Rear panel control	Power on/off switch OSD membrane switch
Mounting Type	Panel mount or VESA (100mm) mount
Connectors	1 x VGA port 1 x DP port 1 x DVI-D port (share with HDMI) 1 x HDMI port (share with DVI-D) 1 x USB Type B for touchscreen 1 x 3-pin terminal block DC power input 1 x 2W speaker (option)
Power supply	Power Input: 9~36V DC power input with external AC power adapter Power Consumption: Max. 18W
Weight	16.53 lb / 7.5 kg
Dimension	21.94"(W) x 14.26"(H) x 2.55"(D)
Environmental	Operating Temperature: 0°C to 50°C (0~40°C for high brightness model) Storage Temperature: -30°C to 70°C Relative Humidity: 10~90% @ 40°C, non-condensing
Certification	CE/FCC, Class A

Available Configurations

Touch Screen

- 21.5-inch resistive-type touch screen RS-232 / USB port
- 21.5-inch Project capacitive-type touch screen USB port

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com