

APH8172

17.3" sunlight readable display with 1920 x 1080 Full HD resolution, VGA + HDMI(no speaker) input, panel or VESA (100mm) mount, 100/240VAC power input, and an aluminum front bezel.

- ▶ 17.3" FHD high brightness industrial LCD monitor
- ▶ Supports 1920 x 1080 native resolution
- ▶ 1000-nits high brightness sunlight readable display
- ▶ VGA + HDMI(no speaker) video input
- ▶ Option for 3G-SDI, or MCS control
- ▶ Option for Resistive or Projected Capacitive touch screen - USB
- ▶ VESA (100 x 100mm) mount ready
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input



Description

The APH8172 is a 17.3" high brightness sunlight readable monitor supporting 1920 x 1080 FHD resolution, 1000-nits high brightness display, and VGA + HDMI(no speaker) video input. Designed to meet professional and industrial demands, the display features an aluminum front bezel, a sunlight-readable display, improved energy efficiency, and a fanless architecture that provides around-the-clock operation. The APH8172 is equipped with a variety of optional features and modules including IP65 rated front bezel, touch screen technology (Resistive or Projected Capacitive touch screen), auto or manual dimming, additional video signals, MCS multi-screen control, and DC power input.

Technical Specifications

SPECIFICATION	VALUE
Material	8mm aluminum front bezel Rear rugged heavy-duty metal construction Option for IP65/NEMA4 rated front bezel
LCD Panel	Size: 17.3 inch Native Resolution: 1920 x 1080 Brightness (cd/m ²): 1000 Contrast Ratio (typ.): 600:1 Colors: 16.7 M, 6-bit Viewing Angle (H/V): 160° x 140° Response Time (ms): 40 Dot Pitch (mm): 0.1989 Display Area (mm): 381.888H x 214.812V Surface Treatment: Hard-coating

Specifications subject to change without notice.

	Surface Hardness: 3H Backlight Type: LED MTBF (hrs): 50,000
Video Input	Standard: VGA + HDMI(no speaker) Option: 3G-SDI input, or MCS multi-display control
Touch screen (Option)	Resistive 1-pt touch screen - USB port Projected Capacitive 10-pt touch screen - USB port Lockable USB connector
Dimming (Option)	Auto dimming or Dimming switch with IP54 protection
Rear panel control	Power on/off switch OSD membrane switch
Mounting Type	VESA (100 x 100mm) mount
Cable	1 x 6ft VGA cable included 1 x Power adapter 1 x Power cord
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 39W, Standby 2W Option for 12V / 24V / 48V / 125V DC power input
Weight	11.4 lb / 5.2 kg
Dimension	18.4"(W) x 2.2"(D) x 13"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com