

APH9190

19" widescreen sunlight readable display with 1440 x 900 resolution, VGA + HDMI(no speaker) input, panel or VESA mount (100mm) mount, 100/240VAC power input, and an aluminum front bezel.

- ▶ 19" widescreen high brightness industrial LCD monitor
- ▶ Supports 1440 x 900 native resolution
- ▶ 1000-nits high brightness sunlight readable display
- ▶ VGA + HDMI(no speaker) video input
- ▶ Option for BNC, Audio, 3G-SDI, or MCS control
- ▶ Option for Resistive 1-pt touch screen - USB
- ▶ VESA (100 x 100mm) mount ready
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input



Description

The APH9190 is a 19" widescreen high brightness sunlight readable monitor supporting 1440 x 900 resolution, 1000-nits high brightness display, and VGA + HDMI(no speaker) video input. Designed to meet professional and industrial demands, the display features an aluminum front bezel, a sunlight-readable display, improved energy efficiency, and a fanless architecture that provides around-the-clock operation. The APH9190 is equipped with a variety of optional features and modules including IP65 rated front bezel, Resistive touch screen, auto or manual dimming, additional video signals, MCS multi-screen control, and DC power input.

Technical Specifications

SPECIFICATION	VALUE
Material	8mm aluminum front bezel Rear rugged heavy-duty metal construction Option for IP65 / NEMA 4 rated front bezel
LCD Panel	Size: 19 inch Native Resolution: 1440 x 900 Brightness (cd/m ²): 1000 Contrast Ratio (typ): 1000:1 Colors: 16.7 M Viewing Angle (H/V): 160° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.2835 Display Area (mm): 408.24H x 255.15V Surface Treatment: Haze 25%, Hard-coating

Specifications subject to change without notice.

	Surface Hardness: 3H Backlight Type: LED MTBF (hrs): 50,000
Video input	Standard: VGA + HDMI(no speaker) Option: BNC, 3G-SDI input, or MCS multi-display control
Touch screen (Option)	Resistive 1-pt touch screen - USB port Lockable USB connector
Dimming (Option)	Auto dimming or Dimming switch with IP54 protection
Rear panel control	Power on/off switch OSD membrane switch
Mounting Type	VESA (100 x 100mm) mount
Cable	1 x 6ft VGA cable included 1 x Power adapter 1 x Power cord
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 34 Watt, Standby 4 Watt Option for 12V / 24V / 48V / 125V DC power input
Weight	15.4 lb / 7 kg
Dimension	20"(W) x 2.6"(D) x 13.3"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Available Configurations

LCD monitor

- 19" 1440 by 900 wide screen LCD monitor

Power Supply

- 110/220VAC power adapter
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter

OSD menu control

- Single OSD menu control
- MCS Multi-display OSD menu control via serial / RJ45 port

Touch Screen

- N/A
- 19-inch wide screen resistive-type touch screen with USB port

Specifications subject to change without notice.

- 19-inch wide screen capacitive-type touch screen with USB port

Auto / Switch dimming

- N/A
- Auto dimming
- Switch dimming

Video Input

- VGA + DVI-D
- VGA + DVI-D + BNC + S-Video + Audio + remote controller
- VGA + HDMI W/ speaker + BNC + S-Video + Audio + remote controller

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com