

APM5200

20" industrial LCD monitor supporting 1600 x 1200 native resolution, VGA + HDMI (no speaker) video input, VESA (100mm) mount, 100/240VAC power input, and an aluminum front bezel.

- ▶ 20" industrial LCD monitor
- ▶ Supports 1600 x 1200 native resolution
- ▶ VGA + HDMI (no speaker) video input
- ▶ Option for HDMI, Audio, 3G-SDI, or MCS
- ▶ Option for Resistive 1-pt touch screen - USB
- ▶ Option for front IP65 / NEMA4 rated protection
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V / 125V DC power input



Description

The APM5200 is a 20" industrial LCD monitor supporting 1600 x 1200 resolution and VGA + HDMI (no speaker) video input. Designed to meet professional and industrial demands, the display features an aluminum front bezel, improved energy efficiency, and a fanless architecture that provides around-the-clock operation. The APM5120 is equipped with a variety of optional features and modules including an IP65 rated front bezel, Resistive touch screen, additional input modules, and DC power input.

Technical Specifications

SPECIFICATION	VALUE
Material	8mm aluminum front bezel Rear rugged heavy-duty metal construction Option for IP65/NEMA4 rated front bezel
LCD Panel	Size: 20 inch Native Resolution: 1600 x 1200 Brightness (cd/m ²): 300 Contrast Ratio (typ): 800:1 Colors: 16.7 M Viewing Angle (H/V): 178° x 178° Response Time (ms): 16 Dot Pitch (mm): 0.255 Display Area (mm): 408H x 306V Surface Treatment: Anti-glare, Hard-coating Surface Hardness: 3H

Specifications subject to change without notice.

	Backlight Type: CCFL MTBF (hrs): 45,000
Video input	Standard: VGA + HDMI (no speaker) Option: HDMI, Audio, 3G-SDI input, or MCS multi-display control
Touch Screen (Option)	Resistive 1-pt touch screen - USB port Lockable USB connector
Rear panel control	Power on/off switch OSD membrane switch
Mounting Type	VESA (100 x 100mm) mount
Cable	1 x 6ft VGA cable included 1 x Power adapter included 1 x Power cord included
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 45W, Standby 4W Option for 12V / 24V / 48V / 125V DC power input
Weight	15.4 lb / 7 kg
Dimension	20.2"(W) x 2.8"(D) x 15.4"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Available Configurations

LCD monitor

- 20" 1600 by 1200 LCD screen

IP65 & NEMA 4 rated front bezel

- N/A
- IP65 & NEMA 4 rated front bezel

Video Input

- VGA + DVI-D
- VGA + DVI-D + BNC + S-Video + Audio + remote controller
- VGA + HDMI W/ speaker + BNC + S-Video + Audio + remote controller
- VGA + DVI-D + Quad Display (4 BNC in/out channel)
- VGA + DVI-D + TV tuner (analog input)

OSD menu control

- Single OSD menu control
- MCS Multi-display OSD menu control via serial / RJ45 port

Specifications subject to change without notice.

Power Supply

- 110/220VAC power adapter
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter

Touch Screen

- N/A
- 20-inch resistive-type touch screen with USB port

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com