

APW4013

13.3" industrial LCD monitor with 3840 x 2160 4K UHD resolution, DP 1.2 + HDMI 1.4 + HDMI 2.0 video input, VESA (100mm) mount, and rugged aluminum front bezel.

- ▶ 13.3" 4K UHD industrial LCD monitor
- ▶ Supports 3840 x 2160 native resolution
- ▶ DP 1.2 + HDMI 1.4 + HDMI 2.0 video input
- ▶ Option for 3G-SDI input or MCS multi-display control
- ▶ Option for Resistive or PCAP touch screen - USB
- ▶ Option for video decoding capability up to 1080P
- ▶ PIP sub-screen & PBP dual-screen viewing efficiency
- ▶ VESA (100 x 100mm) mount ready
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input



Description

The APW4013 is a 13.3" industrial LCD monitor featuring 3840 x 2160 4K resolution, DP 1.2 + HDMI 1.4 + HDMI 2.0 video input, panel or VESA mount, and a rugged aluminum front bezel ensuring high mobility. This monitor has a variety of embedded modules including HDMI decoder, HDMI extender, multi-monitor OSD controller, and 3G-SDI input. These optional embedded modules give you the ability to remotely manage video and transmission for multiple monitors over a network. With reduced energy and a fanless architecture, the APW4013 provides professional-use durability and around-the-clock operation.

Technical Specifications

SPECIFICATION	VALUE
Construction	8mm aluminum front bezel Rear rugged metal enclosure Option for IP65 / NEMA4 rated front bezel
LCD Panel	Size: 13.3 inch Native Resolution: 3840 x 2160 Brightness (cd/m ²): 340 Contrast Ratio (typ.): 1500:1 Colors: 16.7 M, 8-bit Viewing Angle (H/V): 178°x 178° Response Time (ms): 29 Dot Pitch (mm): 0.0765

Specifications subject to change without notice.

	Display Area (mm): 293.76H x 165.24V Surface Treatment: Glare Surface Hardness: 3H Backlight Type: 3H MTBF (hrs): 15,000
Video Input	Standard: DP 1.2 + HDMI 1.4 + HDMI 2.0 Option: 3G-SDI or MCS multi-display control
Touch Screen (Option)	Resistive 1-pt touch screen - USB port Projected Capacitive 10-pt touch screen - USB port Lockable USB connector
HDMI Modules (Option)	HDMI decoder module 1080P over IP HDMI receiver module 1080P HDMI quad display module 1080P
Rear Panel	Power on/off switch OSD membrane switch
OSD Menu Control	OSD membrane switch control for Picture, Position, Color, OSD Set, Reset, PIP, and MISC
Mounting Type	VESA (100 x 100mm) mount
Cable	1 x 6ft DP cable included 1 x Power adapter included 1 x Power cord included
Power Supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 9W, Standby 2W Option for 12V / 24V / 48V / 125V DC power input
Weight	TBD
Dimension	14"(W) x 2.2"(D) x 9.9"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com