

# FES8098

Fanless embedded PC with Celeron N3350 1.1GHz CPU, dual LAN, 6 x USB, 4 x COM ports, 1 x VGA, 1 x DP, and 12V DC power input in an ultra-slim rugged enclosure.

- ▶ Ultra-slim fanless embedded computer
- ▶ Intel Celeron N3350 1.1GHz dual-core CPU
- ▶ 4GBDDR3L SO-DIMM memory (Max. 8GB)
- ▶ Dual LAN, 6 x USB, 4 x COM ports, 1 x VGA, 1 x DP
- ▶ Supports 1 x 2.5" SSD & 1 x full-size mSATA slot
- ▶ VESA (75 x 75mm) mounting holes
- ▶ 12V DC power input, option for power adapter
- ▶ Option for Windows 10 Pro OS



## Description

Ultra-slim fanless embedded computer powered by Celeron N3350 1.1GHz CPU comes with 8GB DDR3L memory, 1 x 2.5" SATA SSD, 1 x full-size mSATA slot, dual LAN, 6 x USB, 4 x COM, 1 x VGA, 1 x DP, and 12V DC power input. Option for external AC power adapter.

## Technical Specifications

SPECIFICATION	VALUE
Construction	Ultra-slim fanless rugged enclosure
System	CPU: Celeron N3350 1.1GHz dual-core Memory: 4GB DDR3L SO-DIMM, Max. 8GB Storage: 1 x 2.5" SATA III SSD
Expansion Slot	1 x full-size mSATA slot (with SATA & USB signal) 1 x full-size mPCIe slot (with PCIe & USB signal)
Front I/O Port	2 x USB 2.0 2 x RS-232 (COM1 / COM3) 1 x RS-232/422/485 (COM2) 1 x Power LED, 1 x HDD LED 1 x Power Button
Rear I/O Port	4 x USB 3.0 1 x RS-232 (COM4) 1 x VGA, 1 x DP

*Specifications subject to change without notice.*

2 x LAN by Intel I210  
1 x line-out  
1 x 3-pin DC terminal block (lockable)

<b>Power Supply</b>	12V DC power supply Option for external power adapter
<b>Weight</b>	4.41 lb / 2 kg
<b>Dimension</b>	8.56"(W) x 1.77"(H) x 5.83"(D)
<b>Mounting</b>	VESA (75mm) mounting holes on top
<b>Environmental</b>	Operating Temperature: 0°C to 60°C Storage Temperature: -40°C to 85°C Humidity: 20% ~ 90%
<b>Compliance</b>	CE, FCC

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)