

KD81912

19" 1280 x 1024 rackmount LCD keyboard drawer with 12-port DVI-D KVM switch and 104-key keyboard with touchpad in a 1U high 24.4" depth rackmount sliding drawer.

- ▶ 19" rack LCD console drawer
- ▶ Supports 1280 x 1024 native resolution
- ▶ 104-key keyboard with 2-button touchpad - USB
- ▶ Integrated 12-port DVI-D KVM switch
- ▶ 1 x local console
- ▶ Option for 6ft or 15ft DVI-D USB KVM cables
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V / 125V DC power input
- ▶ 1U high 24.4" (620mm) depth rackmount drawer



Description

Rackmount LCD console drawer with a 19 inch 1280 x 1024 industrial LCD monitor, 104-key keyboard with touchpad, 12-port DVI-D KVM switch, and a 1U high 24.4 inch depth rackmount drawer. The rack console features a slim design with molded front handle, configurable on-screen display (OSD), and hotkey combination. Option for 6ft or 15ft DVI-D + USB KVM cables and MAC or SUN keyboard layout.

Technical Specifications

| SPECIFICATION | VALUE |
|---------------|--|
| Material | Heavy-duty steel |
| LCD Monitor | Size: 19 inch Native Resolution: 1280 x 1024 Brightness (cd/m ²): 250 Contrast Ratio: 1000:1 Colors: 16.7 M Viewing Angle (H/V): 170° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.294 Display Area (mm): 376.32H x 270.33V Surface Treatment: Haze 25%, Hard-coating Surface Hardness: 3H Backlight: LED MTBF (hrs): 30,000 |

Specifications subject to change without notice.

| | |
|---------------------------------------|---|
| Keyboard & pointing device | 104-key keyboard with touchpad (combo free) |
| KVM port | Number of Ports: 12 x DVI KVM ports Connector: DVI-D connector + USB 3.0 connector (for keyboard, mouse & audio) |
| KVM Usage | Advanced user profiles and configurable on screen display (OSD) & hotkey combination Multilingual on screen display menu Supports eight characters password protection |
| Front Panel Control | Power on/off switch OSD (on screen display) 1 x bank number LED indicator 12 x KVM ports LED indicators for on-line / Active / Remote 10 x KVM channel membrane buttons 1 x bank membrane button |
| Compatibility | Hardware: HP / IBM / Dell PC, Server and Blade Server, SUN / MAC OS Support: Windows / Linux / Unix / Mac OS |
| Cables (Option) | Option for 6ft or 15ft DVI-D + USB KVM cable |
| Power supply | Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 55W, Standby 34W |
| Color | Black (RAL 9005) |
| Weight | 30.1 lb / 13.7 kg |
| Dimension | 17.4"(W) x 24.4"(D) x 1.73"(H) |
| Environmental | Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration |
| Compliance | FCC, CE, RoHS, TAA Compliant |

Available Configurations

LCD monitor

- 19" 1280 by 1024 LCD screen

keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

12 port DVI KVM switch

- 12 port DVI KVM switch with 6 x DVI KVM cables

DVI-KVM-cable

- N/A
- 1 x DVI KVM cable

Specifications subject to change without notice.

- 4 x DVI KVM cables
- 6 x DVI KVM cables

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com