

KD82212

20.1" 1600 x 1200 industrial LCD monitor with 12-port DVI-D KVM switch, 104-key keyboard with touchpad, and 100/240VAC power input in a 1U high 25.6" depth rackmount drawer.

- ▶ 20.1" rack LCD console drawer
- ▶ Supports 1600 x 1200 native resolution
- ▶ 104-key keyboard with 2-button touchpad - USB
- ▶ Integrated 12-port DVI-D KVM switch
- ▶ 1 x local console
- ▶ Option for 6ft or 15ft DVI-D USB KVM cables
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V / 125V DC power input
- ▶ 1U high 25.6" (650mm) depth rackmount drawer



Description

KVM rack console with a 20.1 inch 1600 x 1200 industrial LCD monitor, front OSD functions, and a 1U slim design with a molded front handle. The rack console is integrated with a 12-port DVI-D KVM switch that provides easy installation and streamlined access to servers and systems. Option for 6ft or 15ft DVI-D + USB KVM cables.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 20.1 inch Native Resolution: 1600 x 1200 Brightness (cd/m ²): 300 Contrast Ratio (typ.): 800:1 Colors: 16.7 M Viewing Angle (H/V): 178° x 178° Response Time (ms): 16 Dot Pitch (mm): 0.255 Display Area (mm): 408H x 306V Surface Treatment: Anti-glare, Hard-coating Surface Hardness: 3H Backlight: CCFL MTBF (hrs): 45,000
Keyboard & pointing device	104-key keyboard with 2-button touchpad (combo free)

Specifications subject to change without notice.

KVM port	Number of Ports: 12 x DVI KVM ports Connector: DVI-D connector + USB 3.0 connector (for keyboard, mouse & audio)
KVM Usage	Advanced user profiles and configurable on screen display (OSD) & hotkey combination Multilingual on screen display menu Supports eight characters password protection
Front Panel Control	Power on/off switch OSD (on screen display) 1 x bank number LED indicator 12 x KVM ports LED indicators for on-line / Active / Remote 10 x KVM channel membrane buttons 1 x bank membrane button
Compatibility	Hardware: HP / IBM / Dell PC, Server and Blade Server, SUN / Mac OS Support: Windows / Linux / Unix / Mac OS
Cables (Option)	Option for 6ft or 15ft DVI-D + USB KVM cable
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 78W, Standby 34W
Color	Black (RAL 9005)
Weight	34.1 lb / 15.5 kg
Dimension	17.3"(W) x 25.6"(D) x 1.73"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Available Configurations

LCD monitor

- 20" 1600 by 1200 LCD screen

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter

12 port DVI KVM switch

- 12 port DVI KVM switch with 6 x DVI KVM cables

DVI-KVM-cable

- N/A
- 1 x DVI KVM cable
- 4 x DVI KVM cables

Specifications subject to change without notice.

- 6 x DVI KVM cables

Audio input with speaker

- No speaker
- Audio input with speaker

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com