

# KD85174

17.3" 3840 x 2160 4K LCD console with an 8 port HDMI KVM switch, dual slide rails, and keyboard with touchpad in a 1U high 25.6" depth rackmount drawer.

- ▶ 1U 25.6" depth rackmount drawer
- ▶ 17.3" 3840 x 2160 4K LCD panel
- ▶ 8 port HDMI KVM switch
- ▶ HDMI 2.0 + USB ports
- ▶ 104-key keyboard with touchpad
- ▶ Dual slide rail design
- ▶ Option for 6ft HDMI or DP KVM cable
- ▶ 100/240VAC power adapter



## Description

NOTICE! : PRODUCT EOL. PLEASE VISIT 4K KVM SWITCH - RACK KVM CONSOLE FOR RELATED PRODUCTS. Rack console comes with a 17.3 inch 3840 x 2160 4K LCD panel, 8-port HDMI KVM Switch, 104-key keyboard with touchpad, dual slide rails, and a 1U high 25.6 inch depth rackmount drawer. Option for HDMI / DP KVM cable, keyboard with trackball, and DC power input.

## Technical Specifications

| SPECIFICATION | VALUE  |
|---------------|--|
| Material      | Heavy-duty steel   |
| LCD Panel     | Size: 17.3 inch<br>Resolution: 3480 x 2160<br>Brightness: 400<br>Contrast Ratio: 1000:1<br>Display Area (mm): 382.12H x 214.94V<br>Viewing Angle (H/V): 178° x 178°<br>Response Time (ms): 16<br>Dot Pitch (mm): 0.0995<br>Backlight: LED<br>Colors: 16.7M, 8-bit<br>Surface Treatment: Anti-Glare<br>Surface Hardness: 3H<br>MTBF: 20,000 hours |
| Video Input   | HDMI 2.0   |

*Specifications subject to change without notice.*

|                                       |  |
|---------------------------------------|--|
| <b>Drawer Design</b>                  | Dual slide rails for monitor and keyboard drawer<br>Monitor and keyboard slide out independently   |
| <b>Keyboard &amp; pointing device</b> | 104-key keyboard integrated with 3-button touchpad<br>Option for trackball   |
| <b>KVM Switch</b>                     | HDMI 2.0 KVM switch<br>Front button & keyboard hotkey  |
| <b>KVM Port</b>                       | 8 x HDMI 2.0 + USB-B (Video + KB / MS)<br>16 : 9 – 3840 x 2160 @ 60Hz<br>16 : 10 – 1920 x 1200 @ 60Hz<br>4 : 3 – 1600 x 1200 @ 60Hz  |
| <b>KVM Cable (Option)</b>             | 6ft HDMI KVM cable<br>6ft DP KVM cable   |
| <b>Front Panel Control</b>            | Power on/off switch<br>OSD (on-screen display)   |
| <b>Power Supply</b>                   | 100/240VAC power input, 50/60 Hz<br>Consumption: Max. 38W<br>Option for DC power input   |
| <b>Color</b>                          | Black  |
| <b>Weight</b>                         | 28.6 lb (Net) / 41.8 lb (Gross)  |
| <b>Dimension</b>                      | 17.4"(W) x 25.6"(D) x 1.73"(H)   |
| <b>Environmental</b>                  | Operation Temperature: 0° to 55°C<br>Storage Temperature: -20° to 60°C<br>Shock: 10G acceleration (11ms duration)<br>Vibration: 10 ~ 300Hz 0.5G RMS random vibration<br>Relative Humidity: 5-90%, non-condensing<br>Altitude: 16,000ft, operating; 40,000ft, non-operating |
| <b>Safety</b>                         | CE, FCC, RoHS2   |

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)