KDF81712

17.3" 1920 x 1080 FHD rackmount LCD console drawer with a 12-port DVI-D KVM switch, 104-key keyboard with touchpad, and a 1U high 22.8" depth sliding drawer.

- 17.3" Full HD rack LCD console drawer
- Supports 1920 x 1080 native resolution
- 104-key keyboard with 2-button touchpad - USB
- Integrated 12-port DVI-D KVM switch
- 1 x local console
- Option for 6ft or 15ft DVI-D USB KVM cables
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- Option for 12V / 24V / 48V / 125V DC power input
- 1U high 22.8" (580mm) depth rackmount drawer

Description

Rackmount LCD console drawer with a 17.3 inch 1920 x 1080 Full HD LED backlight LCD monitor, 104-key keyboard with 2-button touchpad, and a 1U high 22.8 inch depth rackmount drawer. The rack console is integrated with a 12-port DVI-D KVM switch with 1 x local console. Option for DVI-D + USB KVM cables.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 17.3" Native Resolution: 1920 x 1080 Brightness (cd/m²): 300 Contrast Ratio (typ.): 1000: 1 Colors: 16.7 M, 8-bit Viewing Angle (H/V): 178° x 178° Response Time (ms): 25 Dot Pitch (mm): 0.1989 Display Area (mm): 381.888H x 214.812V Surface Treatment: Anti-glare, Hard-coating Surface Hardness: 3H Backlight: LED MTBF (hrs): 15,000
Keyboard & pointing device	104-key keyboard with 2-button touchpad - USB

Specifications subject to change without notice.

KVM Port	Number of Ports: 12 x DVI KVM ports Connector: DVI-D connector + USB 3.0 connector (for keyboard, mouse & audio)
KVM Usage	Advanced user profiles and configurable on- screen display (OSD) & hotkey combination Multilingual on-screen display menu Supports eight character password protection
Front Panel Control	Power on/off switch OSD (on screen display) 1 x bank number LED indicator 12 x KVM ports LED indicators for on-line / Active / Remote 10 x KVM channel membrane buttons 1 x bank membrane button
KVM Cables (Option)	Option for 6ft or 15ft DVI-D + USB KVM cables
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 45W, Standby 34W Option for 12V / 24V / 48V / 125V DC power input
Color	Black (RAL 9005)
Weight	25.5 lb / 11.6 kg
Dimension	17.4"(W) x 22.8"(D) x 1.73”(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Available Configurations

keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

LCD monitor

- 17.3" 1920 by 1080 full HD LCD screen

12 port DVI KVM switch

- 12 port DVI KVM switch with 6 x DVI KVM cables

DVI-KVM-cable

- N/A
- 1 x DVI KVM cable
- 4 x DVI KVM cables
- 6 x DVI KVM cables

Power Supply

- 110/220VAC power supply

Specifications subject to change without notice.

- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

Request a Quote or Learn More

Contact us at **info@acnodes.com** or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.