

# KDR-4K17

17.3" 4K UHD multi-display rackmount console drawer with dual or triple displays, a 104-key keyboard with touchpad, DP 1.2 input, and a 2U high rack enclosure.



- ▶ 2U multi-display rackmount display drawer
- ▶ Dual or triple 17.3" 4K UHD industrial LCD panels
- ▶ Supports 3840 x 2160 native resolution
- ▶ 104-key keyboard with touchpad
- ▶ DP 1.2 video input w/ attached 6ft DP cable
- ▶ Option for HDMI video input (per panel)
- ▶ Built-in solid bearing slide rails & dual stereo speaker
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V DC power input



## Description

The KDR-4K17 is a 2U 4K multi-display console drawer featuring 17.3" 4K LCD monitors supporting 3840 x 2160 native resolution, Display Port 1.2 video inputs with attached 6ft DP cables, a 104-key keyboard with touchpad, and 100/240VAC power input in a 2U high rack enclosure.

## Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 17.3 inch Resolution: 3480 x 2160@60Hz Brightness (cd/m <sup>2</sup> ): 400 Contrast Ratio (typ.): 1000:1 Display Area (mm): 382.12H x 214.94V Viewing Angle (H/V): 178° x 178° Response Time (ms): Max. 16 Dot Pitch (mm): 0.0995 Colors: 16.7M, 8-bit Surface Treatment: Anti-Glare Surface Hardness: 3H Backlight Type: LED MTBF (hrs): 15,000
LCD Mounting Position	KDR-4K17-2L: Dual display (left hinged mount)

*Specifications subject to change without notice.*

KDR-4K17-2R: Dual display (right hinged mount)  
KDR-4K17-3: Triple display

<b>KB &amp; MS</b>	104-key keyboard with touchpad pointing device Option for trackball pointing device
<b>Video Input</b>	Standard: DP 1.2 video input w/ attached 6ft DP cable (per panel) Option: HDMI 2.0 video input (per panel)
<b>Front Panel Control</b>	Power on/off switch OSD (on-screen display)
<b>Drawer Design</b>	Built-in solid bearing slide rails Mounting Distance: 21.7~31.1 inch (550~790 mm)
<b>Power Supply</b>	Input: Auto-sensing 100 to 240VAC, 50/60Hz Consumption Per Panel: Max. 21W, Saving Mode 2W Option for 12V / 24V / 48V DC power input
<b>Color</b>	Black
<b>Weight</b>	Dual Display: 46.2 lb / 21 kg Triple Display: 56.5 lb / 25.7 kg
<b>Dimension</b>	Product: 17.4"(W) x 21.7"(D) x 3.5"(H) Packing: 22.8"(W) x 26.9"(D) x 7.8"(H)
<b>Environmental</b>	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
<b>Compliance</b>	CE, FCC, RoHS, TAA

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)