KDS6198

19 inch 1280 x 1024 / 1152 x 900 rack LCD console with a 104-key keyboard with Sun keys, 8 port KVM switch, and a 1U high 24.5 inch depth rackmount drawer.

- 1U high & 24.5 inch depth rackmount drawer
- 19 inch 1280 x 1024 industrial LCD panel
- Supports 1152 x 900 Sun native resolution
- 104-key keyboard with Sun function keys & 10-key keypad
- 3-button touchpad, option for trackball
- 8 port USB KVM switch
- 110/220VAC power supply adapter

Description

NOTICE: PRODUCT CURRENTLY UNAVAILABLE. PLEASE VISIT SUN MICRO RACK LCD CONSOLE FOR RELATED PRODUCTS. Rack KVM console supporting 1280 x 1024 and 1152 x 900 display resolution with an 8 port KVM switch and Sun function keyboard designed for industrial IPC applications.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
Keyboard and Touchpad	SUN-compatible keyboard integrated with 3-button touchpad Option for keyboard with trackball
LCD Panel	Size: 19" Resolution: 1280 x 1024 Sun resolution: 1152x900 Auto switch between Sun and PC display resolution Brightness: 300nit Contrast Ratio: 1000 : 1 Response time: Tr=1.3ms Display Area: 338 x 270mm Viewing Angle: 160° Horizontal and 160° Vertical Backlight: 4 CCFTs Colors: 16.7M colors MTBF: 50,000 hours
Video Input	Analog RGB, 0.7Vp-p

Specifications subject to change without notice.

Plug & Play DDC	EDID 1.3
Resolution	720 x 400, 70Hz 640 x 480, 60/ 70/ 72/ 75 Hz 800 x 600, 60/ 70/ 72/ 75Hz 1024 x 768, 60/ 70/ 75 Hz 1152 x 864, 60/ 70/ 75Hz 1280 x 720, 60/ 75Hz 1280 x 1024, 60/ 70/ 75 Hz 1152 x 900, 66/ 76Hz
KVM Switch	8 port USB KVM switch Connector type: proprietary DB-15 KVM connector Cascades level: 8 levels, up to 128 servers Resolution: 1,600 x 1,200 Supprot hot-plug cable and built-in KVM switch buttons Multi-platform: Mix PCs, Suns, PCs, IBMs, HPs, Compaq & DELL O/S support: Windows Vista/ 2003/ XP/ 2000, Linux, Netware, Unix
KVM Management	Multilingual OSD: English, France, German, Spanish, Italian, Russian, Simplified Chinese, Japanese Hot key combination: Scroll-lock, Cap-lock, Num-Lock, Alt, Ctrl & Win Security: Password enable & disable, up to 8 users profile for port access PC Selection: Front button, OSD menu & hotkey
KVM switch Connector	8 x D-Sub 15 pin (female) for VGA / Keyboard /mouse (Combo Interface, USB or PS/2) 1 x D-sub 15 pin for cascades port
Cable	8 x 6' 4-in-1 KVM cable for VGA / Keyboard /mouse Option for 10' or 15' KVM side: 1 x D-sub 15 pin proprietary KVM connector Server side: 1 x D-sub 15 pin VGA and 1 x USB or 2 x PS/2 connectors
Drawer Design	High load-rating slide rail with angle bracket Extension up to 31.1inch depth Option for extension bracket up to 36 inch depth
Power supply	Auto-sensing 100 to 240VAC, 50/60Hz Max. 48Watt, Standby 5W
DC Power (Option)	DC Power input with 12V, 24V, 48V selection
Color	Black
Environmental	Operating Temperature: 0°C to 50°C Storage Temperature: -5°C to 60°C Humidity: 5~90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
Weight	33 lb
Safety	FCC, CE
Dimension	17.4"(W) x 24.5"(D) x 1.73"(H)

Available Configurations

Specifications subject to change without notice.

LCD monitor

- 19" 1280 by 1024 / 1152 by 900 LCD

8 port KVM switch

- 8 by port DB-15 PS/2 KVM switch
- 8 port DB-15 combo free KVM switch
- 8 port DB-15 combo free + 1 remote console KVM switch
- 8 port DB-15 combo free + 1 IP console KVM switch

keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

Request a Quote or Learn More

Contact us at info@acnodes.com or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.