

# KDW81912

19" 1440 x 900 widescreen rack LCD console with a 12 port DVI KVM switch and 104-key keyboard with touchpad in a 1U high 22.8" short-depth rackmount drawer.

- ▶ 19" widescreen rack LCD console drawer
- ▶ Supports 1440 x 900 native resolution
- ▶ 104-key keyboard with 2-button touchpad - USB
- ▶ Integrated 12-port DVI-D KVM switch
- ▶ 1 x local console
- ▶ Option for 6ft or 15ft DVI-D USB KVM cables
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V / 125V DC power input
- ▶ 1U high 22.8" (580mm) depth rackmount drawer



## Description

Rackmount LCD console drawer with a 19 inch 1440 x 900 widescreen LED backlight LCD monitor, 104-key keyboard with touchpad, and a 1U high 22.8 inch short-depth rackmount drawer. The rack console is integrated with a 12-port DVI-D KVM switch and supports 1 x local user console. Option for DVI-D + USB KVM cable and MAC or SUN keyboard layout.

## Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 19 inch Native Resolution: 1440 x 900 Brightness (cd/m <sup>2</sup> ): 250 Contrast Ratio (typ): 1000:1 Colors: 16.7 M Viewing Angle (H/V): 170° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.2835 Display Area (mm): 408.24H x 255.15V Surface Treatment: Anti-glare Surface Hardness: 3H Backlight: LED MTBF (hrs): 30,000

*Specifications subject to change without notice.*

<b>Keyboard &amp; pointing device</b>	104-key keyboard with 2-button touchpad (combo free)
<b>KVM port</b>	Number of Ports: 12 x DVI KVM ports Connector: DVI-D connector + USB 3.0 connector (for keyboard, mouse & audio)
<b>KVM Usage</b>	Advanced user profiles and configurable on screen display (OSD) & hotkey combination Multilingual on-screen display menu Supports eight characters password protection
<b>Front Panel Control</b>	Power on/off switch OSD (on screen display) 1 x bank number LED indicator 12 x KVM ports LED indicators for on-line / Active / Remote 10 x KVM channel membrane buttons 1 x bank membrane button
<b>Cables (Option)</b>	Option for 6ft or 15ft DVI-D + USB KVM cables
<b>Power supply</b>	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 55W, Standby 34W Option for 12V / 24V / 48V / 125V DC power input
<b>Color</b>	Black (RAL 9005)
<b>Weight</b>	28 lb / 12.5 kg
<b>Dimension</b>	17.4"(W) x 22.8"(D) x 1.73"(H)
<b>Environmental</b>	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
<b>Compliance</b>	CE, FCC, RoHS, TAA Compliant

## Available Configurations

### LCD monitor

- 19" 1440 by 900 wide screen LCD monitor

### keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

### 12 port DVI KVM switch

- 12 port DVI KVM switch with 6 x DVI KVM cables

### DVI-KVM-cable

- N/A
- 1 x DVI KVM cable
- 4 x DVI KVM cables
- 6 x DVI KVM cables

*Specifications subject to change without notice.*

## Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)