

# KDX81712

16.2" 1920 x 1200 WUXGA rack LCD console drawer with a 12-port DVI-D KVM switch and 104-key keyboard with touchpad in a 1U high 22.8" depth rackmount sliding drawer.

- ▶ 1U high 22.8 inch depth rackmount drawer
- ▶ 16.2 inch 1920 x 1200 WUXGA industrial LCD monitor
- ▶ 104-key keyboard with 2-button touchpad
- ▶ 12-port DVI-D KVM switch
- ▶ Option for 6ft or 15ft DVI-D + USB KVM cables
- ▶ Slim design with molded front handle & short depth drawer design
- ▶ Configurable on-screen display (OSD) & hotkey combination
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input



## Description

Rackmount LCD console drawer with 16.2 inch 1920 x 1200 industrial LED backlight LCD monitor, 104-key keyboard with touchpad, 12-port DVI-D KVM switch, and a 1U high 22.8 inch depth rackmount drawer. Option for DVI-D + USB KVM cables and MAC or SUN keyboard layout.

## Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 16.2 inch Resolution: 1920 x 1200 Brightness (cd/m <sup>2</sup> ): 300 Contrast Ratio (typ.) : 800:1 Display Area (mm): 343.8H x 214.9V Viewing Angle (H/V): 178° x 178° Colors: 16.7M, 8-bit Backlight: LED MTBF (hrs): 20,000
Video Input	DVI-D video input
Keyboard & pointing device	104-key keyboard with 2-button touchpad (combo free)
Keyboard Layout (Option)	Option MAC or SUN keyboard layout

*Specifications subject to change without notice.*

<b>KVM port</b>	12 x DVI KVM ports (1 x DVI, 1 x USB 3.0 port for keyboard & mouse)
<b>KVM Usage</b>	Advanced user profiles and configurable on screen display (OSD) & hotkey combination Multilingual on screen display menu Supports eight characters password protection
<b>Front Panel Control</b>	Power on/off switch OSD(on screen display) 1 x bank number LED indicator 12 x KVM ports LED indicators for on-line / Active / Remote 10 x KVM channel membrane buttons 1 x bank membrane button
<b>Cables (Option)</b>	Option for 6ft or 15ft DVI-D + USB KVM cables
<b>Power supply</b>	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 59W, Standby 29W
<b>Color</b>	Black (RAL 9005)
<b>Weight</b>	26.6 lb / 12.1 kg
<b>Dimension</b>	17.4"(W) x 22.8"(D) x 1.73"(H)
<b>Environmental</b>	OperatingTemperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
<b>Safety</b>	CE, FCC

## Available Configurations

### keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

### LCD monitor

- 17" 1920 by 1200 full HD LCD screen

### 12 port DVI KVM switch

- 12 port DVI KVM switch with 6 x DVI KVM cables

### DVI-KVM-cable

- N/A
- 1 x DVI KVM cable
- 4 x DVI KVM cables
- 6 x DVI KVM cables

### Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter

Specifications subject to change without notice.

- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)