

MKD6117

17.3" 1920 x 1080 FHD rackmount LCD console drawer with an 8 port KVM switch and 104-key keyboard with touchpad in a 1U high 22.8" depth rackmount drawer.

- ▶ 1U high 22.8 inch depth rackmount drawer
- ▶ 17.3 inch 1920 x 1080 Full HD LCD monitor
- ▶ VGA video input
- ▶ 8 port KVM switch
- ▶ 1 x local user console
- ▶ 104-key keyboard with touchpad pointing device
- ▶ Option for 6ft VGA + USB KVM cables
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input



Description

The MKD6117 is a 17.3" rack KVM console supporting 1920 x 1080 FHD resolution with 16.7M colors. The console features a short-depth design that allows you to mount into only a 1U standard 19" rack mount space. The rack console features an integrated 8-port VGA KVM switch and keyboard with a touchpad pointing device. Users can easily control the monitor using the front OSD controls and keyboard hotkeys. Designed to meet professional and environmental demands, the MKD6117 is designed to allow users to control and switch between computers in an environment from a convenient 1U rack mount solution.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 17.3 inch Max Resolution: 1920 x 1080 Brightness (cd/m ²): 300 Contrast Ratio (typ.): 1000:1 Viewing Angle: 178° x 178° Display Aarea (mm): 381.888H x 214.812V Colors: 16.7 M, 8-bit Backlight: LED MTBF (hrs): 15,000
Video Input	VGA video input

Specifications subject to change without notice.

Keyboard & Pointing device	104-key keyboard with 2-button touchpad
KVM Port	8 x KVM ports (1 x VGA, USB or PS/2 for keyboard & mouse)
KVM switch	Advanced user profiles and configurable on screen display (OSD) & hotkey combination Multilingual on screen display menu Supports eight characters password protection
Local Console	1 x VGA port (resolution up to 1600 x 1200) 2 x USB ports for Keyboard & Mouse
Cascade port	1 x in / out proprietary cascade KVM port Extended up to 128 servers by 8-level cascade
Color	Black (RAL 9005)
Front Panel Control	Power on/off switch OSD (on screen display) 1 x bank number LED indicator 8 x KVM ports LED indicators for On-line / Active / Remote 10 x KVM channel membrane buttons 1 x bank membrane button
KVM Cables (Option)	Option for 6ft / 10ft / 15ft VGA + USB KVM cables
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 45W, Standby 34W
Weight	25.5 lb / 11.6 kg
Dimension	17.4"(W) x 22.8"(D) x 1.73"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Available Configurations

keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter

LCD monitor

- 17.3" 1920 by 1080 full HD LCD screen

Specifications subject to change without notice.

KVM switch

- 8 port KVM switch
- 16 port KVM switch

User Console

- 1 local
- 1 local + 1 x remote with receiver
- 1 local + 1 x IP with RJ45 port

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com