MKD6117M

17.3" 1920 x 1080 Full HD rack LCD console with 8 port Matrix KVM switch and 104-key keyboard with touchpad in a 1U high 22.8" depth rackmount drawer.

- 1U high 22.8 inch depth rackmount drawer
- 17.3 inch 1920 x 1080 Full HD industrial LCD monitor
- 104-key keyboard with 2-button touchpad
- VGA video input
- 8-port Matrix DB-15 KVM switch, option for 16-port KVM switch
- 2 x user consoles (1 x local + 1 x remote with receiver)
- Option for 6ft / 10ft / 15ft VGA + USB KVM cables
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input

Description

Rackmount LCD console drawer with 17.3 inch 1920 x 1080 Full HD industrial LCD monitor, VGA video input, 104-key keyboard with touchpad, and a 1U high 22.8 inch depth rackmount drawer. The rack console is integrated with an 8-port Matrix DB-15 KVM switch with 2 x user consoles (1 x local console + 1 x remote console). Option for 16-port Matrix DB-15 KVM switch, remote or IP user console, and VGA + USB KVM cables.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 17.3 inch Max. Resolution: 1920 x 1080 Brightness (cd/m²): 300 Contrast Ratio (typ.): 1000:1 Viewing Angle (H/V): 178° x 178° Active Area (mm): 381.888H x 214.812V Colors: 16.7 M, 8-bit Backlight: LED MTBF (hrs): 15,000
Video Input	VGA video input
Keyboard & pointing device	104-key keyboard with 2-button touchpad (combo free)
KVM ports	8 / 16 x Matrix KVM ports (1 x VGA, USB or PS/2 for keyboard & mouse)

Specifications subject to change without notice.

KVM Usage	Use console access server independently & simultaneously Advanced user profiles and configurable on screen display (OSD) & hotkey combination Multilingual on screen display menu Supports eight characters password protection
Front Panel Control	Power on/off switch OSD (on screen display) 1 x bank number LED indicator 8 / 16 x KVM ports LED indicators for on-line / Active / Remote 10 x KVM channel membrane buttons 1 x bank membrane button
Local Console	1 x VGA port (resolution up to 1600 x 1200) 2 x USB ports for keyboard & mouse
Remote Console WithReceiver (Option)	Connector: 1 x DB 15-pin VGA port Input Device: 2 x USB ports for keyboard & mouse Remote I/O: 1 x RJ-45 port via Cat6 cable up to 150 meters Cable: 1 x 6ft VGA + USB KVM cable for receiver box Receiver: 1 x receiver box for remote console
IP Remote Console (option)	Connector: RJ45 Ethernet User Management: 15-user login, 1 x active user Network Protocol: DHCP / BOOTP / DNS Security: SSL v3, RSA, AES, HTTP / HTTPs, CSR Browser: Internet Explorer, Firefox, Safari, Netscape
Cascade port	1 x in / out proprietary cascade KVM port Extended up to 128 servers by 8-level cascade
Cables (Option)	Option for 6ft / 10ft / 15ft VGA + USB KVM cables
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 45W, Standby 34W
Color	Black (RAL 9005)
Weight	25.5 lb / 11.6 kg
Dimension	17.4"(W) x 22.8"(D) x 1.73”(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5-90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Safety	CE, FCC

Available Configurations

keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

Power Supply

- 110/220VAC power supply

Specifications subject to change without notice.

- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter

LCD monitor

- 17.3" 1920 by 1080 full HD LCD screen

Matrix KVM switch

- 8 port KVM switch
- 16 port KVM switch

User Console

- 1 local + 1 x remoter with receiver
- 1 local + 2 x remote with receiver
- 1 local + 3 x remote with receiver
- 1 local + 1 x remoter with receiver + 1 x IP
- 1 local + 2 x remoter with receiver + 1 x IP
- 1 local + 1 x remoter with receiver + 2 x IP

Request a Quote or Learn More

Contact us at **info@acnodes.com** or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.