

MKD6219D

19" 1440 x 900 widescreen rack LCD console with an 8-port VGA KVM switch and 104-key keyboard with touchpad in a 1U high 22.8" depth rackmount drawer.

- ▶ 19" widescreen rack LCD console drawer
- ▶ Supports 1440 x 900 native resolution
- ▶ VGA video input
- ▶ 104-key keyboard with 2-button touchpad - USB
- ▶ Integrated 8-port VGA KVM switch, option for 16-port
- ▶ Local console, option for remote or IP console
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V / 125V DC power input
- ▶ 1U high 22.8" (580mm) depth rackmount drawer



Description

The MKD6219D is a 19-inch widescreen rack LCD console drawer with an integrated 104-key keyboard with touchpad and 8-port VGA KVM switch. The display supports 1440 x 900 resolution, 250-nits brightness, 1000:1 contrast ratio, and 16.7 million colors. The console supports 8 or 16 DB-15 KVM ports, 1 x local console, and 1 x in / out propriety cascade KVM port. Optional upgrades include a 16-port VGA KVM switch, remote or IP user console, and MAC or SUN keyboard layout.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 19 inch Native Resolution: 1440 x 900 Brightness (cd/m ²): 250 Contrast Ratio (typ): 1000:1 Colors: 16.7 M Viewing Angle (H/V): 170° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.2835 Display Area (mm): 408.24H x 255.15V Surface Treatment: Anti-glare Surface Hardness: 3H Backlight: LED

Specifications subject to change without notice.

	MTBF (hrs): 30,000
Keyboard & pointing device	104-key keyboard with 2-button touchpad - USB port Option for keyboard with trackball or SUN keys
KVM Port	Number of Ports: 8 or 16 Connector: DB-15 combo connector Connectivity: USB 2-in-1 KVM cable, up to 6, 10 & 15 feet
Local Console	Connector: 1 x VGA Input Device: 2 x USB ports for keyboard & mouse
Remote Console (Option)	Connector: 1 x DB 15-pin, VGA Input Device: 2 x USB type A for keyboard & mouse Remote I/O: 1 x RJ-45 port via Cat6 cable up to 150 meters Receiver Box: 1 x receiver box for remote console Cable: 1 x 6ft VGA + USB KVM cable for receiver box
IP Remote Console (Option)	Connector: RJ45 Ethernet User Management: 15-user login, 1 x active user Network Protocol: DHCP / BOOTP / DNS Security: TLS 1.3, AES, LDAP, Active Directory (AD), HTTP(s) Browser: Chrome, Firefox, Edge, etc. Resolution: 16: 9 - max. 1920 x 1080 / 16:10 - max. 1920 x 1200 / 4: 3 - max. 1600 x 1200
KVM Cascade	1 x in / out proprietary cascade KVM port Extended up to 128 servers by 8-level cascade
KVM Usage	Multilingual OSD: English, France, German, Spanish, Italian, Russian, Chinese, Japanese Hotkey Combination: Scroll-lock, Cap-lock, Num-lock, Alt, Ctrl & Win Security: Password enable & disable, up to 8 users profile for port access PC Selection: Front button, OSD menu & hotkey
Front Panel Control	Power on/off switch OSD (on screen display) 1 x bank number LED indicator 8 / 16 x KVM ports LED indicators for Online / Active 10 x KVM channel membrane buttons 1 x bank membrane button
Compatibility	Hardware: HP / IBM / Dell PC, Server and Blade Server, SUN / Mac OS Support: Windows / Linux / Unix / Mac OS
KVM Cables (Option)	KVM cables not included Option for 6ft / 10ft / 15ft VGA + USB KVM cables
Power Supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 55W, Standby 34W
Color	Black (RAL 9005)
Weight	28 lb / 12.5 kg
Dimension	17.4"(W) x 22.8"(D) x 1.73"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft

Specifications subject to change without notice.

Shock: 10G acceleration (11ms duration)
Vibration: 10~300Hz 0.5G RMS random vibration

Compliance

CE, FCC, RoHS, TAA Compliant

Available Configurations

LCD monitor

- 19" 1440 by 900 wide screen LCD monitor

keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter

KVM switch

- 8 port KVM switch
- 16 port KVM switch

User Console

- 1 local
- 1 local + 1 x remote with receiver
- 1 local + 1 x IP with RJ45 port

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com