MKD91712

17" 1280 x 1024 rack LCD console with a 104-key keyboard with wire optical mouse, 12-port DVI-D KVM switch, 100/240VAC power input, and a 1U high 25.6" dept rackmount drawer.

- 1U high 25.6 inch depth rackmount drawer
- 17 inch 1280 x 1024 industrial LCD monitor
- 104-key keyboard with wired optical mouse
- 12-port DVI-D KVM switch
- Option for 6ft or 15ft DVI-D + USB KVM cables
- Slim design with molded front handle and 2-point lock
- Configurable on-screen display (OSD) & hotkey combination
- Auto-sensing 100 to 240VAC, 50 / 60Hz power input

Description

Rackmount LCD console drawer with a 17 inch 1280 x 1024 LED backlight LCD monitor, 104-key keyboard with wired optical mouse, 12-port DVI-D KVM switch, 1 x local user console, and a 1U high 25.6 inch depth rackmount drawer. Option for 6ft or 15ft DVI-D + USM KVM cables.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 17 inch Resolution: 1280 x 1024 Brightness (cd/m²): 250 Contrast Ratio (typ): 1000 : 1 Display Area (mm): 337.92H x 270.33V Viewing Angle (H/V): 170° x 160° Colors: 16.7 M Backlight: LED MTBF (hrs): 30,000
Video Input	DVI-D video input
Keyboard & optical mouse	104-key keyboard integrated with wired optical mouse
KVM port	12 x DVI KVM ports (1 x DVI, 1 x USB 3.0 port for keyboard & mouse)

Specifications subject to change without notice.

KVM Usage	Advanced user profiles and configurable on screen display (OSD) & hotkey combination Multilingual on screen display menu Supports eight characters password protection
Front Panel Control	Power on/off switch OSD (on screen display) 1 x bank number LED indicator 12 x KVM ports LED indicators for on-line / Active / Remote 10 x KVM channel membrane buttons 1 x bank membrane button
Cables (Option)	Option for 6ft or 15ft DVI-D + USB KVM cables
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max 55W, Standby 34W
Color	Black (RAL 9005)
Weight	42 lb / 19.1 kg
Dimension	17.4"(W) x 25.6"(D) x 1.73”(H)
Environmental	Operating Temperature: 0° to 55°C Storage Temperature: -20° to 60°C Relative Humidity: 5~90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Safety	CE, FCC

Available Configurations

LCD monitor

- 17" 1280 by 1024 LCD screen

keyboard + Point Device

- Wired optical mouse
- Wireless optical mouse

Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter

12 port DVI KVM switch

- 12 port DVI KVM switch with 6 x DVI KVM cables

DVI-KVM-cable

- N/A
- 1 x DVI KVM cable
- 4 x DVI KVM cables
- 6 x DVI KVM cables

Specifications subject to change without notice.

Request a Quote or Learn More

Contact us at info@acnodes.com or call **(909) 597-7588**

www.acnodes.com

Specifications subject to change without notice.