

PCH8270

27" 1920 x 1080 stainless steel panel PC with an IP67/69K rated stainless steel enclosure, Celeron N2930 1.83GHz CPU, capacitive type touch screen, and AC power input.

- ▶ Full IP67/69K rated rugged stainless steel enclosure
- ▶ 27 inch 1920 x 1080 LED backlight LCD monitor
- ▶ Capacitive type touch screen
- ▶ Intel Celeron N2930 1.83GHz processor
- ▶ Option for Core i5 5200U/Core i7 6600U
- ▶ 2 x USB + 1 x LAN + 1 x COM port
- ▶ 110/240VAC power input, option for DC power input
- ▶ Extended working temperature -10°C to 55°C



Description

Stainless steel panel PC with a 27 inch 1920 x 1080 300-nit LCD display, IP67/69K rated anti-corrosion stainless steel enclosure, Celeron N2930 1.83GHz CPU, capacitive type touch screen, and 110/240VAC power input. Option for high brightness display, optical bonding, WiFi & Bluetooth module, and DC power input.

Technical Specifications

| SPECIFICATION | VALUE |
|---------------|---|
| Material | SUS316 stainless steel IP67/69K rated anti-corrosion stainless steel |
| LCD panel | Size: 27 inch Max Resolution: 1920 x 1080 Brightness (cd/m ²): 300 Contrast Ratio (typ.): 3000:1 Viewing Angle (H/V): -89~89 (H); -89~89 (V) Colors: 16.7M Option for high brightness / optical bonding |
| Touch screen | Capacitive-type touch screen |
| System | CPU: Celeron N2930 1.83GHz (std) Option for Core i5 5200 / Core i7 6700 Memory: 1 x 4GB DDR3 SO-DIMM (Max.8GB) Storage: 1 x 128GB SSD (Max.250GB) Ethernet: 1 x Gigabit LAN |

Specifications subject to change without notice.

| | |
|------------------------------------|--|
| | Option for WiFi and Bluetooth module |
| Connectors - C16 / IP Rated | Serial Ports: 1 x RS232 (IP67) USB Ports: 2 x USB (IP67) Ethernet: 1 x RJ45 GbE LAN (IP67) Power: 1 x AC Input (IP66) IP66 rated 6ft extended cables included for each I/O |
| Power Supply | 110/240VAC power input Power Consumption: 55W (typ) Option for 9 to 36V DC input |
| Weight | 30.86 lb / 14 kg |
| Dimension | 27.17"(W) x 2.08"(D) x 17.67"(H) |
| Mounting | VESA mount (75mm / 100mm / 200mm x 100mm) Option for panel mount with gasket |
| Environmental | Operating Temperature: -10°C to 55°C (14°F to 131°F) Relative Humidity: 10% to 95%, non-condensing |
| IP Rating | Full-IP67/69K rated protection |

Available Configurations

Hard Drive

- 64GB SSD
- 250GB SSD

Operating system

- No O.S.
- Windows 7 Pro 64bit
- Windows 10 Pro 64bit

Memory

- 4GB memory
- 8GB memory

CPU

- Celeron N2930 1.83GHz CPU
- Core i5 5200 2.2GHz CPU
- Core i7 6600U 2.6GHz CPU

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com