

# PMH8170

17" 1280 x 1024 1000-nit sunlight readable LCD monitor with VGA + DVI-D video input, 100/240VAC power input, and an open frame metal enclosure.

- ▶ 17" high brightness open frame LCD monitor
- ▶ Supports 1280 x 1024 native resolution
- ▶ 1000-nits high brightness sunlight readable display
- ▶ VGA + DVI-D video input
- ▶ Option for HDMI, BNC, Audio, 3G-SDI, or MCS control
- ▶ Option for Resistive or PCAP touch screen - USB
- ▶ Universal & VESA (100 x 100mm) mount ready
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input



## Description

The PMH8170 is a 17" high brightness open frame monitor supporting a 1000-nits high brightness display, 1280 x 1024 resolution, and 16.7 million colors that achieve excellent picture quality. Designed with improved energy efficiency and around-the-clock operation, the PMH8170 is designed to meet a wide range of industrial and environmental demands.

## Technical Specifications

SPECIFICATION	VALUE
Material	Heavy duty steel
LCD Panel	Size: 17 inch Native Resolution: 1280 x 1024 Brightness (cd/m <sup>2</sup> ): 1000 Contrast Ratio (typ): 1000:1 Colors: 16.7 M Viewing Angle (H/V): 170° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.264 Display Area (mm): 337.92H x 270.33V Surface Treatment: Haze 25%, Hard-coating Surface Hardness; 3H Backlight Type: LED MTBF (hrs): 50,000
Video Input	Standard: VGA + DVI-D

*Specifications subject to change without notice.*

Option: HDMI, BNC, 3G-SDI input, or MCS multi-display control

<b>Touch screen (option)</b>	Resistive 1-pt touch screen - USB port Projected Capacitive 10-pt touch screen - USB port Lockable USB connector
<b>Dimming (Option)</b>	Auto dimming or Dimming switch with IP54 protection
<b>Rear panel control</b>	Power on/off switch OSD membrane switch
<b>Mounting Type</b>	Universal mount or VESA (100mm) mount
<b>Cable</b>	1 x 6ft VGA cable included 1 x Power adapter 1 x Power cord
<b>Power supply</b>	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max. 30W, Standby 4W Option for 12V / 24V / 48V / 125V DC power input
<b>Weight</b>	10.8 lb / 4.9 kg
<b>Dimension</b>	17.2"(W) x 2.3"(D) x 13.9"(H)
<b>Environmental</b>	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
<b>Compliance</b>	FCC, CE, RoHS, TAA Compliant

## Available Configurations

### LCD monitor

- 17" 1280 by 1024 LCD screen

### OSD menu control

- Single OSD menu control
- MCS Multi-display OSD menu control via serial / RJ45 port

### Auto / Switch dimming

- N/A
- Auto dimming
- Switch dimming

### Touch Screen

- N/A
- 17-inch resistive-type touch screen with USB port
- 17-inch capacitive-type touch screen with USB port
- 17-inch Project capacitive-type 10-point multi-touch screen USB port

### Video Input

*Specifications subject to change without notice.*

- VGA + DVI-D
- VGA + DVI-D + BNC + S-Video + Audio + remote controller
- VGA + HDMI W/ speaker + BNC + S-Video + Audio + remote controller

### Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)