


# PMN80120

12.1" waterproof stainless steel monitor with 1024 x 768 resolution, VGA video input, P-CAP multi-touch screen, and an IP66 rated anti-corrosion stainless steel housing.

- ▶ Full IP66 rated anti-corrosion stainless steel housing
- ▶ 12.1 inch 1024 x 768 450-nit industrial LCD monitor
- ▶ Option for 1000-nit high brightness display & optical bonding
- ▶ VGA video input, option for DVI or HDMI input
- ▶ P-cap multi-touch screen with USB
- ▶ Option for Resistive touch screen with USB
- ▶ MIL-STD-810G compliance for shock and vibration
- ▶ 110 to 240VAC power input



## Description

The PMN80120 is a 12.1" waterproof stainless steel touch screen monitor featuring 1024 x 768 display resolution, 500-nits brightness, VGA video input, and a P-CAP multi-touch screen display. Designed with a full IP66 stainless steel enclosure, the monitor can withstand wide temperatures, water projected from jets, and vibration and shock. Option for 1000-nits high brightness, optical bonding, Resistive touch screen, DVI or HDMI input, and 9 to 36V DC power input.

## Technical Specifications

SPECIFICATION	VALUE
<b>Material</b>	SUS316 stainless steel Anti-corrosion stainless steel housing
<b>LCD Panel</b>	Size: 12.1 inch Resolution: 1024 x 768 Brightness (cd/m <sup>2</sup> ): 500-nits Contrast Ratio (typ.): 700:1 Viewing Angle (H/V): 178° x 178° Active Area (mm): 245.76(H) x 184.32(V) Pixel Pitch (mm): 0.24(H) x 0.24(V) Colors: 16.2M Option for 1000-nit high brightness display Option for optical bonding
<b>Video Input</b>	VGA video input

*Specifications subject to change without notice.*

Option for VGA + DVI or VGA + HDMI

<b>Touch Screen</b>	P-CAP type multi-touch screen - USB Option for 5-Wire Resistive type touch screen - USB
<b>On-Screen Display</b>	OSD Input: 5-key OSD buttons OSD Function: Contrast, Color, Position, Auto-adjustment, and Factory Settings
<b>Power Supply</b>	Input: AC 110~240V, Universal, ±10% Power Consumption: 30W (typ.) Option for 9~36V DC power input
<b>Connectors</b>	1 x VGA (IP66 connector) 1 x USB for touch screen (IP66 connector) 1 x 110~240VAC power input (IP66 connector)
<b>Cables</b>	IP66 rated cables for touch screen, video input, and power
<b>Weight</b>	12.1 lb / 5.5 kg
<b>Dimension</b>	13.8"(W) x 11.2"(D) x 1.9"(H)
<b>Mounting</b>	VESA (100 x 100mm) mount
<b>Environmental</b>	Operating Temperature: 0°C to 60°C Storage Temperature: -30°C to 80°C Relative Humidity: 10-95%, non-condensing Vibration: MIL-STD-810G Method 514.6C-3 Shock: MIL-STD-810G Method 516.6 IP Rating: Full IP66

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)