

PMW6215

21.5" open frame LCD monitor with 1920 x 1080 resolution, VGA + HDMI + DVI video input, VESA mount, AC input with built-in power, and an open frame metal enclosure.

- ▶ 21.5 inch widescreen open frame LCD monitor
- ▶ Supports 1920 x 1080 Full HD display resolution
- ▶ 250-nits brightness, option for 1000-nits high brightness
- ▶ VGA + HDMI + DVI input
- ▶ Option for VGA + HDMI + DP input
- ▶ Option for AG glass, AR glass, Resistive touch, Capacitive touch
- ▶ Option for EMI mesh shielding, UV film, sensor, digital signage
- ▶ Option for -10°C to 65°C wide working temperature
- ▶ Wall and VESA (100 x 100mm) mount ready
- ▶ AC input w/ built-in PWR, option for DC-IN



Description

The PMW6215 21.5" open frame monitor is a reliable, cost-effective industrial solution designed for kiosk information systems, industrial automation, self-service, and commercial applications. The monitor supports 1920 x 1080 FHD display resolution, VGA + DVI + HDMI input, an optional built-in touch screen for interactive applications, and AC input w/ built-in PWR. With an open frame modularized design, it provides flexible product configuration and mounting that allows you to custom design enclosures for specific applications and OEM customers.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 21.5 inch Max Resolution: 1920 x 1080 Brightness (cd/m ²): 250-nits Option for 1000-nits high brightness Contrast Ratio (typ.): 1000:1 Viewing Angle (H/V): 170° x 160° Active Area (mm): 476.64(H) x 268.11(V) Pixel Pitch (mm): 0.248(H) x 0.248(V) Response Time: ≤ 5ms Backlight: LED

Specifications subject to change without notice.

	Colors: 16.7M MTBF (hrs): 35,000
LCD Enhancements(Optional)	Option for EMI Mesh Shielding or UV film Option for AG Glass, AR Glass, Resistive touch, or Capacitive touch
Video Input	VGA + HDMI + DVI input Option for VGA + HDMI + DP input
On-Screen Display	5 x OSD buttons for Power On/Off, Auto, Up, Down, Menu Option for external OSD box
Sensor (Option)	Option for light sensor or motion sensor
Digital Signage (Option)	Option for MP-1080P
Power Supply	Input: AC power input with built-in power Operation / Power Saving: 26.25 watt, < 1 watt (Support DPMS) Option for Isolated 9-36V DC-IN or 24V / 48V / 72V / 90V / 125V / 250V DC-IN
Mounting	Wall and VESA (100mm) mount
Weight	17.64 lb / 8 kg
Dimension	20.94"(W) x 13.54"(H) x 2.48"(D)
Environmental	Operating Temperature: 0°C to 50°C Option for -10°C to 65°C wide operating temperature Storage Temperature: -20°C to 60°C Humidity: 10% ~ 90% (no condensation)
Safety	FCC, CE

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com