

RK120D

1U rackmount keyboard drawer with an 8-port VGA KVM switch, 104-key keyboard with 2-button touchpad, and a 1U high 23.6-inch depth rackmount drawer.

- ▶ 1U rackmount keyboard drawer
- ▶ Integrated 8 or 16-port DB-15 KVM switch
- ▶ 104-key keyboard with touchpad - USB interface
- ▶ 1 x local console, option for remote or IP console
- ▶ Option for SUN Micro keyboard layout
- ▶ Enhanced design with molded front panel & two-point lock
- ▶ Adjustable rear mounting bracket & one man installation design
- ▶ 1U 23.6" (600mm) depth rackmount drawer



Description

Rackmount keyboard drawer with an 8-port VGA KVM switch, one local console, and a 104-key keyboard with touchpad in a 1U high 23.6-inch depth rackmount drawer. The keyboard drawer features front mounting holes that allow you to easily mount the drawer into any 19-inch rackmount cabinet or server rack. Option for 16-port VGA KVM switch, remote or IP user console, SUN keyboard layout, and VGA + USB KVM cables.

Technical Specifications

SPECIFICATION	VALUE
Construction	Sealed aluminum chassis Metal with the positive pole processing
Keyboard	Keys: 104-key keyboard Keyboard Indicator: Num lock, Caps lock, Scroll lock Keypad: 17-key numeric keypad Supporting Layout: English (USA) Interface: USB Keys Life Cycle: 20 million
Keyboard Layout	Option for SUN keyboard layout - USB interface
Pointing device	2-button touchpad
KVM Port	Number of Ports: 8 or 16 Connector: DB-15 combo connector Connectivity: USB 2-in-1 KVM cable, up to 6, 10 & 15 feet

Specifications subject to change without notice.

KVM Switch	Use console access server independently & simultaneously Advanced user profiles and configurable on screen display (OSD) & hotkey combination Multilingual on screen display menu Supports 8-character password protection
Local console	Connector: 1 x DB-15 Input Device: 2 x USB ports for keyboard & mouse
Remote Console (Option)	Connector: 1 x DB 15-pin VGA Input Device: 2 x USB ports for keyboard & mouse Remote I/O: 1 x RJ-45 port via Cat6 cable up to 150 meters Receiver Box: 1 x receiver box for remote console Cable: 1 x 6ft VGA + PS/2 KVM cable for receiver box Resolution Support: 16:9 - max. 1920 x 1080 / 16:10 - max. 1920 x 1200 / 4:3 - max. 1600 x 1200
IP Remote Console (Option)	Connector: RJ45 Ethernet User Management: 15-user login, 1 x active user Network Protocol: DHCP / BOOTP / DNS Security: TLS 1.3, AES, LDAP, Active Directory (AD), HTTP(s) Browser: Chrome, Firefox, Edge, etc. Resolution Support: 16: 9 - max. 1920 x 1080 / 16:10 - max. 1920 x 1200 / 4: 3 - max. 1600 x 1200
Cascade Port	1 x in / out proprietary cascade KVM port Extended up to 128 servers by 8-level cascade
Compatibility	Hardware: HP / IBM / Dell PC, Server and Blade Server SUN / Mac OS Support: Windows / Linux / Unix / Mac OS
KVM Cables (Option)	KVM cables not included Option for 6ft / 10ft / 15ft VGA + USB KVM cable
Mounting Distance	560 ~ 790 mm (22 ~ 31.1 inch)
Weight	24 lb / 10.9 kg
Dimension	17.4"(W) x 23.6"(D) x 1.73"(H)
Environmental	Operating Temperature: -20°C to 55°C Storage Temperature: -20°C to 60°C Operating Humidity: 10~90%, non-condensing Storage Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Available Configurations

keyboard + Point Device

- 104-key keyboard with touch pad
- 104-key keyboard with track ball

KVM switch

- 8 port KVM switch

Specifications subject to change without notice.

- 16 port KVM switch

User Console

- 1 local
- 1 local + 1 x remote with receiver
- 1 local + 1 x IP with RJ45 port

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com