

RK120H

1U keyboard drawer with 8-port 2K KVM switch, 1 x local console, 104-key keyboard with touchpad, and a 23.6" depth rack drawer with a molded front panel and two-point lock.

- ▶ 1U rackmount keyboard drawer
- ▶ Integrated 8-port 2K KVM switch
- ▶ 104-key keyboard with touchpad - USB interface
- ▶ 1 x local console
- ▶ Option for SUN Micro keyboard layout
- ▶ Enhanced design with molded front panel & two-point lock
- ▶ Adjustable rear mounting bracket & one man installation design
- ▶ 1U 23.6" (600mm) depth rackmount drawer



Description

The RK120H is a 1U keyboard drawer integrated with an 8-port 2K KVM switch in a 23.6" depth rack drawer. It features a 104-key keyboard with touchpad, 1 x local console, and front mount holes that allow you to easily mount the drawer into a 19" rackmount cabinet or server rack.

Technical Specifications

SPECIFICATION	VALUE
Construction	Sealed aluminum chassis Metal with the positive pole processing
Keyboard	Keys: 104-key keyboard Keyboard Indicator: Num lock, Caps lock, Scroll lock Keypad: 17-key numeric keypad Supporting Layout: English (USA) only Interface: USB Keys Life Cycle: 20 million
Keyboard Layout (Option)	Option for SUN keyboard layout - USB interface
Pointing Device	2-button touchpad
KVM Port	Number of Ports: 8 Connector: HDMI 1.4 + USB-B (Video + KB / MS) Resolution: 16 : 9 - max. 2560 x 1440@60Hz / 16 : 10 - max. 1920 x 1200@60Hz / 4 : 3 - max. 1600 x 1200@60Hz

Specifications subject to change without notice.

Management	PC Selection: Front button & keyboard hotkey
Compatibility	Hardware: HP / IBM / Dell PC, Server and Blade Server, SUN / Mac OS Support: Windows / Linux / Unix / Mac OS
Power Supply	Input: Auto sensing 100 to 240VAC, 50 / 60 Hz Consumption: Max. 10W
KVM Cables (Option)	KVM cables not included Option for 6ft HDMI-USB KVM cable (CH-HDMI) or 6ft DVI-USB KVM cable (CH-DVI)
Mounting Distance	560 ~ 790 mm (22 ~ 31.1 inch)
Weight	24 lb / 10.9 kg
Dimension	17.4"(W) x 23.6"(D) x 1.73"(H)
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Operating Humidity: 10~90%, non-condensing Storage Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA Compliant

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com