

# RMC5210A

2U high rackmount computer with Intel Core Ultra/Core i/AMD Ryzen processors, standard ATX M/B, 7 x low profile PCIe expansion slots, and 4 x drive bays in a 2U high 14.1" short-depth rack chassis.

- ▶ 2U high rackmount computer
- ▶ 14.1" short-depth rackmount chassis
- ▶ Intel Core Ultra / Core i / AMD Ryzen processors
- ▶ Standard ATX motherboard
- ▶ 7 x low profile PCIe expansion slots
- ▶ 8GB RAM (Up to 32GB) & 250GB NVMe M.2 SSD
- ▶ 1 x 5.25" external & 3 x 3.5" internal drive bays
- ▶ Front power ON/OFF switch, LED indicators, 2 x USB ports
- ▶ 600W Flex power supply



## Description

The RMC5210A is a 2U high rackmount computer powered by Intel Core Ultra / Core i / AMD Ryzen processors with a standard ATX motherboard. The system features 1 x 5.25" external drive bay, 3 x 3.5" internal drive bays, and 7 x low profile PCIe expansion slots in a 2U high 14.1" short-depth rack chassis. Designed for small business applications to entry-level server applications, this 2U high rackmount computer is fully customizable and offers various options, including additional storage space, removable drive bays, add-on cards, graphic cards, and more.

## Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy-duty steel cold-rolled steel
Standard ATX M/B	Size: Standard ATX motherboard
Drive Capacity	1 x 5.25" external drive bay 3 x 3.5" internal drive bays
Expansion Slot	7 x low profile PCIe expansion slots
Front Panel Controls	Power ON/OFF Switch System Reset Switch 2 x USB ports

*Specifications subject to change without notice.*

<b>LED Indicators</b>	LED Indicators for Power ON/OFF, LAN, HDD Activity
<b>Power Supply</b>	600W Flex power supply
<b>Color</b>	Black
<b>Weight</b>	25 lb / 11.34 kg
<b>Dimension</b>	19"(W) x 3.5"(H) x 14.1"(D)
<b>Environmental</b>	Operating Temperature: 0°C to 40°C (32°F to 104°F) Relative Humidity: 5% to 95%, non-condensing

## Available Configurations

### Accessory

- No slide rail
- 20" to 26" (adjustable) slide rail

### Dual / Quad Core CPU socket 1155

- Celeron G1610 2.6GHz Dual-Core
- Celeron G1630 2.8GHz Dual-Core
- Pentium G2020 2.9GHz Dual-Core
- Core i3-3240 3.40GHz Dual-Core
- Core i3-3250 3.50GHz Dual-Core
- Core i5-3470 3.2GHz Quad-Core
- Core i5-3570 3.4GHz Quad-Core
- Core i7-3770 3.4GHz Quad-Core

### Optical Drive

- DVD-RW Drive

### Expansion Slot

- 7 x low profile expansion slots

### Hard Drive

- 500GB SATA HD
- 750GB SATA HD
- 1TB SATA HD
- 120GB SATA-2 SSD HD

### Ethernet LAN

- 100/1000 Ethernet LAN

### Audio

- On-Board Audio

### Video

- On-board video

### Operating system

- No O.S.

*Specifications subject to change without notice.*

- Windows 7 Pro 32bit
- Windows XP pro 32bit

## Mother Board

- LGA1155 / H61 / ATX / SKU-5210  
2 x DIMM DDR3 16GB MEM (max)  
Gigabit LAN / VGA / Audio  
4 x USB 2.0 / COM / LPT  
6 x PCI / 1 x PCIE 2.0 X16
- LGA1155 / Z68 / ATX / SKU-07101  
Gigabit LAN / VGA / DVI / Audio / RAID  
6 x USB / 2 x USB 3.0 / eSATA / Optical  
3 x PCI / 2 x PCIE X1 / 1 x PCIE 2.0 (X16) 4 x DIMM 32GB MEM (max)
- LGA1155 / H67 / ATX / SKU-0210  
4 x DIMM DDR3 32GB MEM (max)  
Gigabit LAN / DVI / HDMI / Audio / RAID  
6 x USB / 2 x USB 3.0 / eSATA / Optical  
3 x PCI / 2 x PCIE X1 / 1 x PCIE 2.0 X16
- LGA1155 / Z68 / ATX / SKU-0211  
4 x DIMM 32GB MEM (max)  
Gigabit LAN / DVI / HDMI / Display port / Audio  
6 x USB / 2 x USB 3.0 / eSATA / Optical  
3 x PCI / 2 x PCIE X1 / 2 x PCIE 2.0 (X16/X8)
- LGA1155 / Q67 / Inudstrail ATX M/B / SKU-07111  
4 x DIMM 16GB MEM (max)  
2 x Gigabit LAN / DVI / DIO 8 channel / Audio  
2 x PS/2 / 3 x RS-232 / 1 x RS- (422/485) / 12 x USB  
3 x PCI / 3 x PCIE( 3 x SATA 3 / 2 x SATA 6 / RAID)

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)