

# RMC8351

3U high rackmount computer with a standard ATX M/B, the latest processors, 4 x drive bays, 7 x PCIe expansion slots, and a standard ATX power supply in a 3U high 15.8" depth rackmount chassis.

- ▶ 3U high rackmount computer
- ▶ 15.8 inch depth rackmount chassis
- ▶ Intel Core Ultra / Core i / AMD Ryzen processors
- ▶ Standard ATX motherboard
- ▶ 7 x PCIe expansion slots
- ▶ 16GB RAM (Up to 64GB) & 250GB NVMe M.2 SSD
- ▶ 1 x 3.5" external & 3 x 5.25 external drive bays
- ▶ 2 x cooling fans & front access dual USB ports
- ▶ 2U 600W ATX power supply



## Description

The RMC8351 is a 3U high rackmount computer supporting a standard ATX motherboard with the latest processors. The system includes 1 x 3.5" external, 3 x 5.25" external drive bays, and 7 x PCIe expansion slots in a 3U high 15.8" depth rack chassis for space-limited applications. The 3U high rackmount PC supports front access dual USB ports and two 80mm cooling fans. Designed to serve a wide range of applications, the RMC8351 is fully customizable. It offers options for additional storage space, removable drive bay options, add-on cards, graphic cards, and more.

## Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy duty cold rolled steel
ATX M/B	Standard ATX motherboard Processor: RMC8351-A - Intel Core Ultra Processors RMC8351-B - AMD Ryzen processors RMC8351-C - Core i processors Memory: Up to 64GB
Drive Bays	1 x 3.5" external drive bay 3 x 5.25" external drive bay
Expansion Slot	7 x PCIe expansion slots

*Specifications subject to change without notice.*

<b>Front Panel Control</b>	Power ON/OFF button System Reset button 2 x USB ports
<b>LED Indicator</b>	LED indicators for Power ON/OFF, HDD Activity, and LAN Activity
<b>Cooling Fan</b>	2 x cooling fans
<b>Power Supply</b>	Standard ATX power supply
<b>Color</b>	Black
<b>Weight</b>	30 lb / 13.61 kg
<b>Dimension</b>	19"(W) x 15.8"(D) x 5.2"(H)
<b>Environmental</b>	Operating Temperature: 0°C to 50°C (32°F to 122°F) Humidity: 5~95%, non-condensing

## Available Configurations

### Accessory

- No slide rail
- 20" to 26" (adjustable) slide rail

### Dual / Quad Core CPU socket 1155

- Celeron G1610 2.6GHz Dual-Core
- Celeron G1630 2.8GHz Dual-Core
- Pentium G2020 2.9GHz Dual-Core
- Core i3-3240 3.40GHz Dual-Core
- Core i3-3250 3.50GHz Dual-Core
- Core i5-3470 3.2GHz Quad-Core
- Core i5-3570 3.4GHz Quad-Core
- Core i7-3770 3.4GHz Quad-Core

### Optical Drive

- DVD-RW Drive

### Expansion Slot

- 7 x low profile expansion slots

### Hard Drive

- 500GB SATA HD
- 750GB SATA HD
- 1TB SATA HD
- 120GB SATA-2 SSD HD

### Ethernet LAN

- 100/1000 Ethernet LAN

### Audio

- On-Board Audio

*Specifications subject to change without notice.*

## Video

- On-board video

## Operating system

- No O.S.
- Windows 7 Pro 32bit
- Windows XP pro 32bit

## Power Supply

- 380W auto-switch ATX power supply
- 500W ATX power supply
- 650W ATX power supply

## Mother Board

- LGA1155 / H61 / ATX / SKU-5210  
2 x DIMM DDR3 16GB MEM (max)  
Gigabit LAN / VGA / Audio  
4 x USB 2.0 / COM / LPT  
6 x PCI / 1 x PCIE 2.0 X16
- LGA1155 / Z68 / ATX / SKU-07101 4 x DIMM 32GB MEM (max) Gigabit LAN / VGA / DVI / Audio / RAID 6 x USB / 2 x USB 3.0 / eSATA / Optical 3 x PCI / 2 x PCIEX1 / 1 x PCIE 2.0 (X16)
- LGA1155 / H67 / ATX / SKU-0210  
4 x DIMM DDR3 32GB MEM (max)  
Gigabit LAN / DVI / HDMI / Audio / RAID  
6 x USB / 2 x USB 3.0 / eSATA / Optical  
3 x PCI / 2 x PCIEX1 / 1 x PCIE 2.0 X16
- LGA1155 / Z68 / ATX / SKU-0211  
4 x DIMM 32GB MEM (max)  
Gigabit LAN / DVI / HDMI / Display port / Audio  
6 x USB / 2 x USB 3.0 / eSATA / Optical  
3 x PCI / 2 x PCIEX1 / 2 x PCIE 2.0 (X16/X8)
- LGA1155 / Q67 / Inudstrail ATX M/B / SKU-07111  
4 x DIMM 16GB MEM (max)  
2 x Gigabit LAN / DVI / DIO 8 channel / Audio  
2 x PS/2 / 3 x RS-232 / 1 x RS- (422/485) / 12 x USB  
3 x PCI / 3 x PCIE( 3 x SATA 3 / 2 x SATA 6 / RAID

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)