

RMC8353A

3U high rackmount computer with a standard ATX M/B, the latest processors, 7 x PCIe expansion slots in a 3U high 15.8" depth rackmount chassis, 4 x external drive bays, 2 hot-swappable SATA HD open trays, and 2 cooling fans & front access dual USB ports.

- ▶ 3U high rackmount computer
- ▶ 15.8 inch short depth rackmount chassis
- ▶ Intel Core Ultra / Core i / AMD Ryzen processors
- ▶ Standard ATX motherboard
- ▶ 7 x PCIe expansion slots
- ▶ 16GB RAM (Up to 64GB)
- ▶ 250GB NVMe M.2 SSD
- ▶ 1 x 3.5" external & 3 x 5.25 external drive bays
- ▶ 2 x 3.5" hot-swappable SATA HD open trays
- ▶ 2 x cooling fans & front access dual USB ports
- ▶ 2U 600W ATX power supply



Description

The RMC8353A is a 3U high rackmount computer supporting a standard ATX motherboard with the latest processors. The system features 1 x 3.5" external & 3 x 5.25" external drive bays, 2 x 3.5" hot-swappable SATA HD open trays, 2 x cooling fans & front access dual USB ports, and 7 x PCIe expansion slots in a 3U high 15.8" depth rack chassis. The RMC8353A is a cost-effective, high-performance system that can be fully customized to meet your requirements. Options are available for additional storage space, removable drive bays, add-on cards, graphic cards, and more.

Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy-duty cold-rolled electroplated steel
Standard ATX M/B	Size: Standard ATX motherboard Processor: RMC8353A-A – Intel Core Ultra Processors RMC8353A-B – AMD Ryzen processors RMC8353A-C – Core i processors Memory: Up to 64GB Integrated SATA port

Specifications subject to change without notice.

	USB ports
Storage Device	2 x 3.5" hot-swappable SATA HD open trays
Expansion Slot	7 x PCIe expansion slots
Front Panel Control	Power ON/OFF button System Reset button 2 x USB ports
LED Indicator	LED indicators for Power ON/OFF, HDD Activity, LAN
Cooling Fan	2 x cooling fans
Power Supply	Standard ATX power supply
Color	Black
Weight	38 lb / 17.24 kg
Dimension	19"(W) x 15.8"(D) x 5.2"(H)
Environmental	Operating Temperature: 0°C to 50°C (32°F to 122°F) Humidity: 5~95%, non-condensing

Available Configurations

Accessory

- No slide rail
- 20" to 26" (adjustable) slide rail

Power Supply

- 300W 2U power supply
- 600W 2U power supply

Operating system

- No O.S.
- Windows 7 Pro 64bit
- Windows 10 Pro 64bit

CPU Kaby Lake 7th CPU

- Pentium G4560 3.5GHz
- Core i3-7100 3.9GHz
- Core i3-7320 4.1GHz
- Core i5-7400 3.0GHz
- Core i5-7500 3.4GHz
- Core i5-7600 3.5GHz
- Core i7-7700 3.6GHz

memory

- 8GB (4 x 2GB) memory
- 16GB (4 x 4GB) memory
- 32GB (4 x 8GB) memory

Specifications subject to change without notice.

- 64GB (4 x 16GB) memory

Hard Drive

- 500GB SATA HD
- 1TB SATA HD
- Samsung 850 250GB SSD
- Samsung 850 500GB SSD
- Samsung 850 1TB SSD

Optical Drive

- No DVD-RW Drive
- DVD-RW Drive (24X)
- Blue-ray burner (16X)

Mother Board

- B250-PLUS
G-LAN / VGA + DVI + HDMI / Audio /
6 x USB (2x3.0 + 4x2.0) /
2 x PCI / 2 x PCIe x16 (1 x16 + 1 x4) / 2 x PCIe x1
- H170-PLUS/CSM
G-LAN / DVI + HDMI / Audio / RAID /
4 x USB (2 x 3.0 + 4 x 2.0) /
2 x PCI / 2 x PCIe x16 (1 x16 + 1 x4) / 2 x PCIe x1
- X11SAE-O
2 x G-LAN / DVI + HDMI + DP / Audio / RAID /
2 x USB (2 x 3.0 + 4 x 2.0) / 1 x TPM 2.0 header /
2 x PCI (5V) / 3 x PCIe x16 / 3 x PCIe x1

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com