

# RMW6170

17.3" 1920 x 1080P Full HD rackmount LCD monitor with VGA + HDMI video input and 100/240VAC power input in an 8U high rackmount enclosure.

- ▶ 6U 17.3" FHD rackmount LCD monitor
- ▶ Supports 1920 x 1080 native resolution
- ▶ Front OSD (on-screen display) function
- ▶ VGA + HDMI video input
- ▶ Option for DVI-D, DP, Audio, Speaker, or 3G/HD/SD-SDI input
- ▶ Option for Resistive or Projected Capacitive touch screen - USB
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V / 125V DC power input



## Description

The RMW6170 is a high-quality 6U 17.3" FHD rackmount LCD monitor designed to meet your display needs in any professional setting. Featuring a native resolution of 1920 x 1080, this monitor delivers crystal-clear images that are sure to impress. The front OSD (on-screen display) function allows you to easily adjust the settings to your preference, while the VGA + HDMI video input ensures compatibility with a wide range of devices. Additionally, the RMW6170 also offers the option for DVI-D, DP, Audio, Speaker, or 3G/HD/SD-SDI input, providing you with even more flexibility and versatility.

## Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy-duty steel
LCD panel	Size: 17.3 inch Max Resolution: 1920 x 1080 Brightness (cd/m <sup>2</sup> ): 300 Contrast Ratio (typ.) : 1000:1 Colors: 16.7 M, 8-bit Viewing Angle (H/V): 178° x 178° Response Time (ms): 25 Dot Pitch (mm): 0.1989 Display Area (mm): 381.888H x 214.812V Surface Treatment: Anti-glare, Hard-coating Surface Hardness: 3H Backlight: LED

*Specifications subject to change without notice.*

	MTBF (hrs): 15,000
<b>Video Input</b>	Standard: VGA + HDMI video input Option: DVI-D, DP, Audio, Speaker, or 3G/HD/SD-SDI input
<b>Touch screen (Option)</b>	Resistive 1-pt touch screen - USB port Projected Capacitive 1-pt / 10-pt touch screen - USB
<b>Front panel control</b>	Power on/off switch OSD membrane switch
<b>Connector</b>	1 x VGA + 1 x HDMI
<b>Power Supply</b>	Input: Auto-sensing 100 to 240VAC, 50/ 60Hz Consumption: Max. 14 Watt, Standby 2 Watt Option for 12V / 24V / 48V / 125V DC power input
<b>Mounting</b>	6U high rackmount monitor for a standard 19" wide rackmount cabinet
<b>Color</b>	Black front panel (RAL 9005)
<b>Weight</b>	9.8 lb / 4.5 kg
<b>Dimension</b>	Product: 18.9"(W) x 1.9"(D) x 10.5"(H) Packing: 20.8"(W) x 4.9"(D) x 17.8"(H)
<b>Environmental</b>	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11 ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
<b>Compliance</b>	CE, FCC, RoHS, TAA

## Available Configurations

### LCD monitor

- 17.3" 1920 by 1080 full HD LCD screen

### Touch Screen

- N/A
- 17-inch resistive-type touch screen with USB port

### Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

### Video Input

- VGA + DVI-D
- VGA + DVI-D + HDMI W/speaker

*Specifications subject to change without notice.*

- VGA + DVI-D + HDMI + MCS (multi-display control)

#### **IP65 / NEMA4 rated front bezel**

- N/A
- IP65 / NEMA4 rated front bezel

### **Request a Quote or Learn More**

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call **(909) 597-7588**

[www.acnodes.com](http://www.acnodes.com)