

# RMW7190

19" 1440 x 900 widescreen LCD monitor with VGA + HDMI video input, OSD membrane switch, and 100/240VAC power input in a 7U high rackmount enclosure.

- ▶ 7U 19" widescreen rackmount LCD monitor
- ▶ Supports 1440 x 900 native resolution
- ▶ Front OSD (on-screen display) function
- ▶ VGA + HDMI video input
- ▶ Option for DVI-D, BNC, Audio, Speaker, or 3G-SDI input
- ▶ Option for Resistive 1-pt touch screen - USB
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V / 125V DC power input



## Description

The RMW7190 is a high-quality 7U 19" widescreen rackmount LCD monitor designed for professionals who require superior display quality in a variety of settings. With a native resolution of 1440 x 900, this monitor delivers clear and sharp images that are perfect for a wide range of applications. The RMW7190 supports VGA + HDMI video input and offers a range of input options, including DVI-D, BNC, Audio, Speaker, or 3G-SDI input, making it the perfect solution for use in professional broadcast environments. The RMW7190 is a reliable and robust rackmount LCD monitor that offers exceptional display quality, a wide range of input options, and compatibility with different power inputs. It is the perfect choice for professionals across various industries, including broadcast, industrial, military, and medical settings.

## Technical Specifications

SPECIFICATION	VALUE
Construction	Heavy-duty steel
LCD panel	Size: 19 inch Max Resolution: 1440 x 900 Brightness (cd/m <sup>2</sup> ): 250 Contrast Ratio (typ.) : 1000:1 Colors: 16.7 M Viewing Angle (H/V): 170° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.2835 Display Area (mm): 408.24H x 255.15V Surface Treatment: Anti-glare

*Specifications subject to change without notice.*

	Surface Hardness: 3H Backlight: LED MTBF (hrs): 30,000
<b>Video input</b>	Standard: VGA + HDMI video input Option: DVI-D, BNC, Audio, Speaker, or 3G-SDI input
<b>Touch screen (Option)</b>	Resistive 1-pt touch screen - USB
<b>Connector</b>	1 x VGA + 1 DVI-D
<b>Front panel control</b>	Power on/off switch OSD membrane switch
<b>Power Supply</b>	Input: Auto-sensing 100 to 240VAC, 50/60Hz Consumption: Max. 20 Watt, Standby 2 Watt Option for 12V / 24V / 48V / 125V DC power input
<b>Mounting</b>	7U high rackmount monitor for a standard 19" wide rackmount cabinet
<b>Weight</b>	12.8 lb / 5.8 kg
<b>Dimension</b>	Product: 18.9"(W) x 2.3"(D) x 12.2"(H) Packing: 20.8"(W) x 4.9"(D) x 17.8"(H)
<b>Environmental</b>	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11 ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
<b>Compliance</b>	CE, FCC, RoHS, TAA

## Available Configurations

### LCD monitor

- 19" 1440 by 900 wide screen LCD monitor

### Touch Screen

- N/A
- 19-inch wide screen resistive-type touch screen with USB port
- 19-inch wide screen Capacitive-type touch screen with USB port

### Video Input

- VGA + DVI-D
- VGA + DVI-D + BNC + S-Video + Audio
- VGA + HDMI w/speaker + BNC + S-Video + Audio
- VGA + DVI-D + HDMI w/speaker + MCS (multi-display control)

### Power Supply

- 110/220VAC power supply
- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter

*Specifications subject to change without notice.*

- 110VDC power adapter
- 125VDC power adapter

#### **IP65 / NEMA4 rated front bezel**

- N/A
- IP65 / NEMA4 rated front bezel

### **Request a Quote or Learn More**

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call **(909) 597-7588**

[www.acnodes.com](http://www.acnodes.com)