

RP1195

19" 1280 x 1024 industrial LCD monitor with VGA + HDMI video input, 100/240VAC power input, and a 1U high 19.7" short-depth rackmount monitor drawer.

- ▶ 1U 19" rackmount LCD monitor drawer
- ▶ Supports 1280 x 1024 native resolution
- ▶ Front OSD (on-screen display) function
- ▶ VGA + HDMI video input
- ▶ Option for DVI-D, BNC, Audio, Speaker, or 3G-SDI input
- ▶ Option for Resistive 1-pt touch screen - USB port
- ▶ 19.7" (500mm) short-depth drawer design
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V / 125V DC power input



Description

The RP1195 is a 19" rackmount LCD monitor drawer supporting 1280 x 1024 native resolution, VGA + HDMI video input, and a 100/240VAC power input in a 1U high 19.7" (500mm) short-depth rack drawer. The monitor drawer features an LED touch on-screen display (OSD), providing users with a convenient way to the device settings.

Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 19 inch Resolution: 1280 x 1024 Brightness (cd/m ²): 250 Contrast Ratio (typ): 1000:1 Colors: 16.7 M Viewing Angle (H/V): 170° x 160° Response Time (ms): 5 Dot Pitch (mm): 0.294 Display Area (mm): 376.32H x 270.33V Surface Treatment: Haze 25%, Hard-coating Surface Hardness: 3H Backlight Type: LED MTBF (hrs): 30,000
Touch Screen (Option)	Resistive 1-point touch screen - USB

Specifications subject to change without notice.

Video input	Standard: VGA + HDMI video input Option: DVI-D, BNC, S-Video, Audio, Speaker, or 3D-SDI
Front Panel Controls	Power on/off switch OSD (On Screen Display) control
On Screen Control	Auto-Adjustment for contrast, balance, H-position, V-position, phase, brightness
Mounting Distance	Display Drawer: 20.1 ~ 29.1 inch (510 ~ 740 mm)
Color	Black (RAL 9005)
Power supply	Input: Auto-sensing 100 to 240VAC, 50 / 60Hz Power Consumption: Max 22W, Standby 2W Option for 12V / 24V / 48V / 125V DC power input
Weight	27.5 lb / 12.5 kg
Dimension	Product: 17.4"(W) x 19.7"(D) x 1.73"(H) Packing: 23.1"(W) x 29.3"(D) x 4.7"(H) * All dimensions stated are subject to change if options are selected / integrated to base model part codes
Environmental	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
Compliance	CE, FCC, RoHS, TAA

Available Configurations

LCD monitor

- 19" 1280 by 1024 LCD screen

Touch Screen

- N/A
- 19-inch resistive-type touch screen with RS-232 port
- 19-inch resistive-type touch screen with USB port
- 19-inch Capacitive-type touch screen with RS-232 port
- 19-inch Capacitive-type touch screen with USB port

Video Input

- VGA + DVI-D video input
- VGA + DVI-D + BNC + S-Video video input
- VGA + DVI-D video input + Audio
- VGA + HDMI w/speaker
- VGA + DVI+ HDMI w/speaker

Power Supply

- 110/220VAC power supply

Specifications subject to change without notice.

- 12VDC power adapter
- 24VDC power adapter
- 48VDC power adapter
- 110VDC power adapter
- 125VDC power adapter

Request a Quote or Learn More

Contact us at info@acnodes.com or call (909) 597-7588

www.acnodes.com