

# RPM-HD17

2U 17.3" multi-display rackmount display drawer with 1920 x 1080, VGA + DVI-D input, built-in solid bearing slide rails, and a 2U high 22" depth rack console drawer.

- ▶ 2U multi-display rackmount display drawer
- ▶ Dual or triple 17.3" Full HD industrial LCD panels
- ▶ Supports 1920 x 1080 native resolution
- ▶ VGA + DVI-D video input (per panel)
- ▶ Option for HDMI or 3G-SDI input (per panel)
- ▶ Built-in solid bearing slide rails & front OSD buttons
- ▶ Built-in dual stereo speaker (per panel)
- ▶ Auto-sensing 100 to 240VAC, 50 / 60Hz power input
- ▶ Option for 12V / 24V / 48V DC power input



## Description

The RPM-HD17 is a 2U multi-display drawer featuring 17.3" LCD monitors supporting 1920 x 1080 native resolution, VGA + DVI-D video input, and 100/240VAC power input. The rack monitor drawer has built-in solid bearing slide rails and dual stereo speakers and a 2U short-depth rugged construction for mobility and durability.

## Technical Specifications

SPECIFICATION	VALUE
Material	Heavy-duty steel
LCD Panel	Size: 17.3 inch Max Resolution: 1920 x 1080 Refresh Rate (Hz): 60 Brightness (cd/m <sup>2</sup> ): 300, option for 1000-nit high brightness Contrast Ratio (typ.): 1000:1 Display Area (mm): 381.888H x 214.812V Viewing Angle (H/V): 170° x 170° Response Time (ms): 25 Dot Pitch (mm): 0.1989 Colors: 16.7M, 8-bit Surface Treatment: Anti-glare, Hard-coating Surface Hardness: 3H Backlight: LED MTBF (hrs): 15,000

*Specifications subject to change without notice.*

<b>LCD Mounting Position</b>	RPM-HD17-2L: Dual display (left hinged mount) RPM-HD17-2R: Dual display (right hinged mount) RPM-HD17-3: Triple display
<b>Video Input</b>	Standard: VGA + DVI-D video input (per panel) Option: VGA + HDMI or VGA + 3G-SDI input (per panel)
<b>Front Panel Control</b>	Power on/off switch OSD (on-screen display)
<b>Drawer Design</b>	Built-in solid bearing slide rails Mounting Distance: 21.7~31.1 inch (550~790 mm)
<b>Power Supply</b>	Input: Auto-sensing 100 to 240VAC, 50/60Hz Consumption Per Panel: Max. 14W, Saving Mode 2W Option for 12V / 24V / 48V DC power input
<b>Color</b>	Black
<b>Weight</b>	Dual Display: 42.7 lb / 19.4 kg Triple Display: 53 lb / 24.1 kg
<b>Dimension</b>	Product: 17.4"(W) x 21.7"(D) x 3.5"(H) Packing: 22.8"(W) x 26.9"(D) x 7.8"(H)
<b>Environmental</b>	Operating Temperature: 0°C to 55°C Storage Temperature: -20°C to 60°C Relative Humidity: 5~90%, non-condensing Altitude (Operating / Non-Operating): 16,000 ft / 40,000 ft Shock: 10G acceleration (11ms duration) Vibration: 10~300Hz 0.5G RMS random vibration
<b>Compliance</b>	CE, FCC, RoHS, TAA

## Available Configurations

### Display

- RPM-HD17-2L Dual Display Left Hinged Mount
- RPM-HD17-2R Dual Display Right Hinged Mount
- RPM-HD17-3 Triple Display

### Video Input (Main Display)

- DP + HDMI

### Video Input (Second Display)

- Display Port 1.2
- DP + HDMI

### Video Input (Third Display)

- N/A
- Display Port 1.2
- DP + HDMI

*Specifications subject to change without notice.*

## Request a Quote or Learn More

Contact us at [info@acnodes.com](mailto:info@acnodes.com) or call (909) 597-7588

[www.acnodes.com](http://www.acnodes.com)